


1 LOCATION OF WATER WELL: County: Rice Fraction: NE 1/4 NE 1/4 SW 1/4 Section Number: 9 Township Number: T 21 S Range Number: R 6 E/W

Distance and direction from nearest town or city street address of well if located within city?
From Hutchinson, Ks. 8 1/2 N, 2 W, 2 N, 2 W, 1/2 S, 1/4 E

2 WATER WELL OWNER: Bret Givens
 RR#, St. Address, Box # : 1300 N. Grand Board of Agriculture, Division of Water Resources
 City, State, ZIP Code : Hutchinson, Ks. 67501 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 40 ft. ELEVATION:
 Depth(s) Groundwater Encountered ft. 2 ft. 3 ft.
 WELL'S STATIC WATER LEVEL 6 ft. below land surface measured on mo/day/yr 10-18-04
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield gpm: Well water was ft. after hours pumping gpm
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well STOCK
 Was a chemical/bacteriological sample submitted to Department? Yes No X; if yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded
 Blank casing diameter 5 in. to 20 ft., Dia in. to ft., Dia in. to ft.
 Casing height above land surface 24 in., weight 160# lbs./ft. Wall thickness or gauge No. 214
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 10 Asbestos-Cement
 2 Brass 4 Galvanized Steel 6 Concrete tile 8 RMP (SR) 11 Other (Specify)
 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 7 Wire wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Torch cut 9 Drilled holes 10 Other (specify) ft.
 SCREEN-PERFORATED INTERVALS: From 20 ft. to 40 ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 40 ft. to 18 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Hale Plug
 Grout Intervals: From 18 ft. to 0 ft., From ft. to ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage NONE
 Direction from well? How many feet?

| FROM | TO | LITHOLOGIC LOG | FROM | TO | PLUGGING INTERVALS |
|-----------|-----------|--|------|----|--------------------|
| <u>0</u> | <u>5</u> | <u>Ready Top Soil</u> | | | |
| <u>5</u> | <u>14</u> | <u>fine Sand - Tan & Grey Clay mix 50/50</u> | | | |
| <u>14</u> | <u>38</u> | <u>Tan Clay & Fine Sand</u> | | | |
| <u>38</u> | <u>40</u> | <u>Red Bed</u> | | | |

RECEIVED

NOV 12 2004

BUREAU OF WATER

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-18-04 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 134 This Water Well Record was completed on (mo/day/yr) 10-22-04 under the business name of Rosecrantz Bemis Ent. by (signature) Jesse Dodson