USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

1. Location of well:	County	Fraction			Section number		Township number Range number			
	Rice	1/4	1/4 CNW	1/4	26	i	т 21 s	_R 7	′ • €	
· · · · · · · · · · · · · · · · · · ·					ner of well:		Dwight Engelland			
7 miles East of Sterling, KS Street address of well location if in city: R.R. or					or street:		Route 2			
City, state, zip						code:	Sterling, KS 67579			
4. Locate with "X" in section below: N						6. Bore hole dia. <u>24</u> in. Completion date <u>5—6—77</u> Well depth <u>66</u> ft.				
						7 Cable tool Rotary Driven Dug				
							Hollow rod Jetted BoredX Reverse rotary			
						8. Use: Domestic Public supply Industry				
						X Irrigation Air conditioning Stock				
E						Lawn Oil field water Other				
						9. Casing: Material Steel Height Above or below Threaded Welded _X Surface12 in.				
							Threaded Welded _X Surface 12 in. RMP PVC Weight 30.36s./ft.			
1 Mile							Dia. 16in. to 26 ft. depth!Wall Thickness; inches or			
5. Type and color of material					From	То	Dia in. to ft. dept	h gage No	7 ga.	
							10. Screen: Manufacturer's n			
Top soi	1				Q	3	Type Double-slot	- Diu-	611	
Brown & gray clay				3	16	Slot gauze 1/8	Lengin	10 '		
Brown &	gray cray				Н	10	Set between 26	4114	ft.	
Sand & gravel & thin clay streaks @ 24,33 & 46					16	65	Gravel pack? VES Size range of material 3/8-200			
Red sha	le				65	66	 Static water level: 11 ft. below land surf 	ace Date 3-	mo./day/yr. -2-77	
							12. Pumping level below land		1/C	
	· unasses						ft. after h			
		***					Estimated maximum yield —		- 1	
							13. Water sample submitted:		mo./day/yr.	
							YesX No _ [ate		
							14. Well head completion: Pitless adapter			
							Pitless adapter 15. Well grouted? <u>VCS</u>	Inches a	bove grade	
							With: X Neat cement Bentonite Concrete			
							Depth: From ft. to _			
						1	16. Nearest source of possible contamination: Field ft Type			
							Well disinfected upon complet			
							17. Pump: Manufacturer's name <u>Peer</u>	Not insta	illed	
							Model number 12MB-3	нр_40_	Volts460	
							Length of drop pipe 40	ft. capacity	900 g.p.m.	
						Type: Submersible	<u>X</u> 10	urbine		
						Jet	Re	eciprocating		
(Use a second sheet if needed)							Centrifugal		ther	
18. Elevation: 19. Remarks:						20. Water well contractor's certification: This well was drilled under my jurisdiction and this report				
						is true to the best of my knowledge and belief.				
Topography:						Clarke Well & Eq., Inc. 185				
Hill							Business name Address Great Bend, KS 67530			
Upland							Signed Own Coll 5-9-77			
Valley							Signed Authorized repr	esentative	Date ———	