


1 LOCATION OF WATER WELL: Fraction SW 1/4 SW 1/4 SW 1/4 Section Number 34 Township Number T 21S Range Number R 7 EW
 County: Rice
 Distance and direction from nearest town or city street address of well if located within city?
2 N. Nickerson Kam.

2 WATER WELL OWNER: Carl Burgess
 RR#, St. Address, Box #: RR 2 Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: Sterling Kam. 67579 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 30 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1, 12 ft. 2. ft. 3. ft.
 WELL'S STATIC WATER LEVEL 12 ft. below land surface measured on mo/day/yr 10-27-88
 Pump test data: Well water was 13 ft. after 1 hours pumping 20 gpm
 Est. Yield 50 gpm Well water was 13 ft. after 6 hours pumping 30 gpm
 Bore Hole Diameter 9 in. to 13 ft., and 6 in. to 30 ft.
 WELL WATER TO BE USED AS:
 Domestic Feedlot Oil field water supply Dewatering Injection well
 Irrigation Industrial Lawn and garden only Observation well
 Was a chemical/bacteriological sample submitted to Department? Yes No ; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:
 Steel RMP (SR) Wrought iron Concrete tile Asbestos-Cement Other (specify below)
 PVC ABS Fiberglass
 Blank casing diameter 6 in. to 20 ft., Dia. in. to 20 ft., Dia. in. to 20 ft.
 Casing height above land surface 12 in., weight 250 lbs./ft. Wall thickness or gauge No. 250
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 Steel Stainless steel Fiberglass PVC Asbestos-cement
 Brass Galvanized steel Concrete tile RMP (SR) Other (specify)
 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 Continuous slot Mill slot Wire wrapped Saw cut None (open hole)
 Louvered shutter Key punched Torch cut Drilled holes
 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 20 ft. to 30 ft., From 20 ft. to 30 ft., From 20 ft. to 30 ft.
 GRAVEL PACK INTERVALS: From 20 ft. to 30 ft., From 20 ft. to 30 ft., From 20 ft. to 30 ft.

6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other
 Grout Intervals: From 3 ft. to 13 ft., From 3 ft. to 13 ft., From 3 ft. to 13 ft.
 What is the nearest source of possible contamination:
 Septic tank Lateral lines Pit privy Livestock pens Abandoned water well
 Sewer lines Cess pool Sewage lagoon Fuel storage Oil well/Gas well
 Watertight sewer lines Seepage pit Feedyard Fertilizer storage Other (specify below)
 Insecticide storage
 Direction from well? East How many feet? 100

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	Sandy soil			
2	8	Sandy clay			
8	11	fine sand			
11	14	fine gravel			
14	30	medium gravel			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo/day/year) 10-27-88 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 193 This Water Well Record was completed on (mo/day/yr) 11-12-89 under the business name of Price Water Well by (signature) John Davenport