			WATE	R WELL RECORD	Form WV	VC-5	KSA 82a-		
→		TER WELL:	Fraction				n Number	Township Number	Range Number
County:	Rice	2		NE 1/4 S			2/	T 2/ S	R & E(W)
Distance a	nd direction	from nearest tov	•	ddress of well if loc					
al===		WED 4-		18 W 190	nroe	n	STerli	' <i>n g</i>	
	R WELL OV		m steffe	- •					
RR#, St. A		•	3 W Mon					-	, Division of Water Resources
City, State,		: > > > - <	rling, Ks	67379					
J LOCATE	E WELL'S L IN SECTIO	OCATION WITH							
714 7	114 320110	N BOX.							3
Ī	!	!							yr . 569.7
-	- NW	NE		•				-	oumping $oldsymbol{3}$, $oldsymbol{\circ}$ gpm
	1								oumping gpm
* w -	1		Bore Hole Diam	eter % in.	to %	ج	ft., a	nd	in. to
₹ "	iχ	! ! ! !	WELL WATER	TO BE USED AS:	5 Public				1 Injection well
ī L	_		1 Domestic	3 Feedlot				Dewatering 12	
	- 311	;	2 Irrigation	4 Industrial					
l L	i		Was a chemical/	bacteriological samp	le submitted	to Depa	artment? Yes	s	es, mo/day/yr sample was sub
<u> </u>		5	mitted				Wate	er Well Disinfected? Yes	No
5 TYPE C	F BLANK	CASING USED:		5 Wrought iron	8 C	oncrete	tile	CASING JOINTS: GIU	ied . 午 Clamped
 1 Ste	el	3 RMP (SI	R)	6 Asbestos-Ceme	ent 9 O	ther (sp	ecify below)) We	lded
@PV	C	4 ABS		7 Fiberglass				Thr	eaded
Blank casir	ng diameter	٠	.in. to . 3 . 0 .	ft., Dia	ir	n. to		ft., Dia	. in. to \hdots ft.
Casing heigh	ght above I	and surface	12	.in., weight	2.29		Ibs./ft	. Wall thickness or gauge	No 1.6 . 6
TYPE OF	SCREEN C	R PERFORATION	N MATERIAL:		a	PVC		10 Asbestos-cer	ment
1 Ste	el	3 Stainless	s steel	5 Fiberglass	_	RMP	(SR)	11 Other (specif	y)
2 Bra	ass	4 Galvaniz	ed steel	6 Concrete tile	9	ABS		12 None used (open hole)
SCREEN C	OR PERFO	RATION OPENIN	IGS ARE:	5 Ga	auzed wrappe	ed	/	8)Saw cut	11 None (open hole)
1 Co	ntinuous slo	ot 3 M	lill slot	6 W	ire wrapped			9 Drilled holes	
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)									
SCREEN-PERFORATED INTERVALS: From									
			From						toft.
G	RAVEL PA	CK INTERVALS:	From	2.2 ft. to		3	ft., From	n ft.	toft.
			From	ft. to			ft., From		to ft.
6 GROUT	MATERIA	L: 1 Neat of	cement	2 Cement grout	<u> </u>	Bentonit	e 4 (
Grout Inter	vals: Fro	m . 2	. ft. to 2 .2.	ft., From		ft. to.		ft., From	ft. toft.
What is the	e nearest s	ource of possible	contamination:				10 Livesto	ock pens 14	Abandoned water well
1 Septic tank 4 Lateral lines 7 Pit privy 11 F							11 Fuel st	torage 15	Oil well/Gas well
2 Sev	wer lines	5 Cess	pool	8 Sewage	lagoon		12 Fertiliz	er storage 16	Other (specify below)
⊘ Wa	atertight sev	ver lines 6 Seep	age pit	9 Feedyard				cide storage	
Direction fr	rom well?	5					How man	y feet? 50	
FROM	TO		LITHOLOGIC	LOG	FRO	М	то		INTERVALS
0	フ	Br 51%	ty Clay					And the state of t	
7	9	sand	F						
9	43	sand 4	Grave/						
								., ,	
								1.00	
		<u> </u>							
		L							
									nder my jurisdiction and was
									knowledge and belief. Kansas
					r Well Recor	d was	•	n (mo/day/yr) 5 d	4.3 . T. J
· · · ·	business na		Miller D				by (signatu		5
INSTRUC	CTIONS: Use to h and Environn	ppewriter or ball point pent, Bureau of Water,	pen. PLEASE PRESS I Topeka, Kansas 6662	FIRMLY and FRINT clearly 20-0001. Telephone: 913-2	r. Please fill in bla 196-5545. Send o	anks, und one to WA	erline or circle to	the correct answers. Send top thre NER and retain one for your reco	ee copies to Kansas Department rds.