CORRECTION TO WATER WELL RECORD (WWC-5)

The following correction(s) was made to the attached WWC-5 log, in order to file the item or to rectify lacking or incorrect information.

Fraction (1/4 1/4) Section-Township-Range changed:

listed as near center SE, 10-225-8W
changed to CSE , $10-215-81$
Other changes: Initial statements:
Changed to:
Comments:
verification method: Written & legal descriptions, position on plat map,
verification method: Written & legal descriptions, position on plat map, and Sterling 1:24,000 topo. map. initials: OPJ date: 6/28/20
submitted by: Kansas Geological Survey, Data Resources Library, 1930 Constant Ave., Lawrence, KS 66047-3726 o: Kansas Dept of Health & Environment Bureau of Water Industrial Programs, Bldg 283, Forbes Field, KS 66620

.,				ER WELL RECORD F	orm WWC-5	KSA 82a				
1 LOCATION OF WATER WELL:			Fraction			tion Number	Township		Range Number	
County: Rice Distance and direction from nearest town of				near 4 center 4 SE 14 1			<u> </u>	2 s	<u> R 8 K/w</u>	
					-					
				North, Sterli	ing, KS				/ 11 	
_	R WELL OW		n Englan					REDR)	
•	Address, Box		0 Ave. T						Division of Water Resource	ces
	, ZIP Code			S 67579					27,308	
AN "X"	E WELL'S L IN SECTIOI	OCATION WITH N BOX: N		COMPLETED WELL dwater Encountered 1.						
Ä	- ZW	NE	Pur Est. Yield .10 Bore Hole Dian	C WATER LEVEL 1 (np test data: Well water .00. gpm: Well water neter30 in. toTO BE USED AS:	was was	ft. a ft. a 	fter	hours pu	mping gp mping gp . to	om om
-	i	i.	1 Domestic						Other (Specify below)	
-	SW	>							Other (Specify below)	
1 1	!	4	1		_	•				
<u>ł</u> L			1	l/bacteriological sample su	iomitted to De	-			· ·	iuo
E TYPE	DE DI ANK (CASING USED:	mitted	E Mrought iron	8 Concre		ter Well Disinfe		X No d X Clamped	
의 'TPE'(1 St		JASING USED: 3 RMP (S	·D)	5 Wrought iron 6 Asbestos-Cement					ed	
76 P\		4 ABS	in)				v) 		aded	
			in to 23	ft., Dia						
				. in., weight 1 .6.						
_	-			in., weight						• •
TYPE OF SCREEN OR PERFORATION MATERIAL:				E E'h l				Asbestos-ceme		
1 Steel 3 Stainless steel			5 Fiberglass	•					• •	
2 Br		4 Galvani:		6 Concrete tile	9 AB:	>		None used (or	,	
		RATION OPENIN			d wrapped		8 Saw cut		11 None (open hole)	
	ontinuous slo		fill slot	6 Wire w	• •		9 Drilled hole			
	ouvered shutt		(ey punched	7 Torch		4 5	• •	• ·		
SCHEEN-	PERFURATI	ED INTERVALS:		23 ft. to						
(GRAVEL PA	CK INTERVALS	: From	ft. to ft. to		ft., Fror	n	ft. 1	o	.ft.
-1			From	ft. to		ft., Fron				ft.
	T MATERIAL		cement	X2 Cement grout						
				ft., From	π.					.π.
		ource of possible				10 Livestock pens		Abandoned water well		
1 Septic tank 4 Lateral lines			, ,		11 Fuel storag					
2 Sewer lines 5 Cess poor			•	8 Sewage lagoon		12 Fertilizer storage				
	•	er lines 6 Seep	page pit	9 Feedyard			ticide storage	_		٠.
	from well?	West	LITHOLOGIC	2100	I EDOM 1	How mai	ny feet?	PLUGGING I	NITEDI/ALC	
FROM	то	m		J LOG	FROM	то		Lodding	NICHVALO	
_0	3	Topsoil			1					
3	14	Fine Sa			+					
14	20		Medium		 					
20	60		to Coars	e sand						
60	82	Medium			1					
82	83	Yellow	Shale		1		organization of the second sec			
									THE PERSON NAMED IN COLUMN 1 C	
- -										
	-				 					—-
	ļ									
	ļ				1					
	L				<u> </u>					
7 CONTI	RACTOR'S	OR LANDOWNE	R'S CERTIFICA	TION: This water well wa	s 🐧) construc	cted, (2) reco	nstructed, or (3	i) plugged und	der my jurisdiction and w	/as
				This Water We						
				rigation, Inc						
				TAGETOIL TIME					7,	
INSTRL	JCTIONS: Use ty	pewriter or ball point	pen. PLEASE PRESS	FIRMLY and PRINT clearly. Plea 620-0001. Telephone: 913-296-55	se fill in blanks, u	inderline or circle	the correct answer	s. Send top three	copies to Kansas Department	