

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: County: <u>Rice</u>	Fraction <u>NE</u> 1/4 <u>SW</u> 1/4 <u>NE</u> 1/4	Section Number <u>33</u>	Township Number <u>T 21 S</u>	Range Number <u>R 8</u> <del>E/W</del>
--	---	-----------------------------	----------------------------------	---

Distance and direction from nearest town or city street address of well if located within city?  
 Approx. 1 1/4 miles south of Sterling, KS

2 WATER WELL OWNER: Bill Ball  
 RR#, St. Address, Box # : Rural Route Board of Agriculture, Division of Water Resources  
 City, State, ZIP Code : Sterling, KS 67579 Application Number: not available

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL... 31 ft. ELEVATION: unknown  
 Depth(s) Groundwater Encountered 1. 9 ft. 2.     ft. 3.     ft.  
 WELL'S STATIC WATER LEVEL 9 ft. below land surface measured on mo/day/yr 1/23/86  
 Pump test data: Well water was not ck'd ft. after     hours pumping     gpm  
 Est. Yield \*225 gpm: Well water was     ft. after     hours pumping     gpm  
 Bore Hole Diameter... 24 in. to 31 ft., and     in. to     ft.  
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well  
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well  
 Was a chemical/bacteriological sample submitted to Department? Yes X No    ; If yes, mo/day/yr sample was submitted 7/18/85  
 Water Well Disinfected? Yes     No X

5 TYPE OF BLANK CASING USED:  
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued     Clamped      
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded XX  
 Blank casing diameter 16 in. to 19 ft., Dia     in. to     ft., Dia     in. to     ft.  
 Casing height above land surface 12 in., weight 31.66 lbs./ft. Wall thickness or gauge No. 188  
 TYPE OF SCREEN OR PERFORATION MATERIAL:  
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement  
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)      
 SCREEN OR PERFORATION OPENINGS ARE:  
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes  
 7 Torch cut 10 Other (specify) Doerr Bridge Slot  
 SCREEN-PERFORATED INTERVALS: From 19 ft. to 31 ft., From     ft. to     ft.  
 GRAVEL PACK INTERVALS: From 10 ft. to 31 ft., From     ft. to     ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other      
 Grout Intervals: From 0 ft. to 10 ft., From     ft. to     ft., From     ft. to     ft.  
 What is the nearest source of possible contamination:  
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) FIELD  
 Direction from well? all How many feet?    

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	8	Topsoil & Sandy Brown clay			
8	29	Sand & gravel, med. to coarse			
29	31	Brown clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1/23/86 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 185 This Water Well Record was completed on (mo/day/yr) 1/24/86 under the business name of Clarke Well & Equipment, Inc. by (signature) [Signature]

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

T

EW

SEC.

1/4

1/4

1/4