

WATER WELL RECORD

Form WWC-5

Division of Water Resources; App. No.

1 LOCATION OF WATER WELL: County: Rice Fraction NW 1/4 NW 1/4 SE 1/4 Section Number 21 Township Number T 21 S Range Number R 8 E/W

Distance and direction from nearest town or city street address of well if located within city? 105 S 6th in Sterling Global Positioning Systems (decimal degrees, min. of 4 digits) Latitude: Longitude: Elevation: Datum: Data Collection Method:

2 WATER WELL OWNER: RR#, St. Address, Box #: City, State, ZIP Code: Dick Anderson 105 S 6th Sterling, KS 67579

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 36-section grid with an 'X' in the center section] 4 DEPTH OF COMPLETED WELL: 50 ft. Depth(s) Groundwater Encountered: WELL'S STATIC WATER LEVEL: 10 ft. below land surface measured on 9-4-07. Pump test data: Well water was 17 ft. after 14 hours pumping 100 gpm. Est. Yield: 100 gpm. WELL WATER TO BE USED AS: 5 Public water supply, 8 Air conditioning, 11 Injection well, 1 Domestic, 3 Feedlot, 6 Oil field water supply, 9 Dewatering, 12 Other (Specify below), 2 Irrigation, 4 Industrial, 7 Domestic (lawn & garden), 10 Monitoring well. Was a chemical/bacteriological sample submitted to Department? No. Sample was submitted. Water well disinfected? No.

5 TYPE OF CASING USED: 1 Steel, 2 PVC, 3 RMP (SR), 4 ABS, 5 Wrought Iron, 6 Asbestos-Cement, 7 Fiberglass, 8 Concrete tile, 9 Other (specify below), 10 Asbestos-Cement, 11 Other (Specify). CASING JOINTS: Glued, Clamped, Welded, Threaded. Blank casing diameter: 5 in. to 40 ft., Diameter. Casing height above land surface: 12 in., Weight: 2.25 lbs./ft., Wall thickness or guage No. 160. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel, 2 Brass, 3 Stainless Steel, 4 Galvanized Steel, 5 Fiberglass, 6 Concrete tile, 7 Torch cut, 8 Saw Cut, 9 ABS, 10 Asbestos-Cement, 11 Other (Specify). SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot, 2 Louvered shutter, 3 Mill slot, 4 Key punched, 5 Gauzed wrapped, 6 Wire wrapped, 7 Torch cut, 8 Saw Cut, 9 Drilled holes, 10 Other (specify). SCREEN-PERFORATED INTERVALS: From 40 ft. to 50 ft. GRAVEL PACK INTERVALS: From 23 ft. to 53 ft.

6 GROUT MATERIAL: 1 Neat cement, 2 Cement grout, 3 Bentonite, 4 Other. Grout Intervals: From 3 ft. to 23 ft. What is the nearest source of possible contamination: 1 Septic tank, 2 Sewer lines, 3 Watertight sewer lines, 4 Lateral lines, 5 Cess pool, 6 Seepage pit, 7 Pit privy, 8 Sewage lagoon, 9 Feedyard, 10 Livestock pens, 11 Fuel storage, 12 Fertilizer Storage, 13 Insecticide Storage, 14 Abandoned water well, 15 Oil well/gas well, 16 Other (specify below). Direction from well? S. How many feet? 50.

Table with columns: FROM, TO, LITHOLOGIC LOG, FROM, TO, PLUGGING INTERVALS. Rows: 0-6 Br Clay, 6-14 Sand + Gravel, 14-16 Br + Gr Clay, 16-28 Sand + Gravel, 28-32 Gr Clay, 32-38 Sand + Gravel, 38-40 Br + Gr Clay, 40-56 Sand + Sm Gravel.

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-4-07 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 447. This Water Well Record was completed on (mo/day/year) 9-17-07 under the business name of Miller Drilling by (signature) G Miller.

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. Visit us at http://www.kdhe.state.ks.us/geo/waterwells.