WATE	R WE	LL RECORD	Form W	WC-5	Division of Wate	r Resources App. No	,
1 LOCATION OF WATER WELL:			Fraction		Section Number	Township No.	Range Number
County: Rice			SE ¼ NE ¼ NE			T 21 S	R 8 □E ☑W
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here					Global Positioning System (GPS) information: Latitude: .38.21568		
nom hearest town of intersection. If at owner's address, effects field .					Longitude: 098.23452 (in decimal degrees)		
					Elevation: 1683		
2 WATER WELL OWNER: Chris Anderson					Datum: ☐ WGS 84, ☐ NAD 83, ☑ NAD 27 Collection Method:		
RR#, Street Address, Box #: 2225 14th Road					GPS unit (Make/Model: Garmin)		
City, State, ZIP Code : Sterling, Kansas 67579					Digital Map/Photo, Topographic Map, Land Survey		
Est. Accuracy: □ <3 m, □ 3-5 m, □ 5-15 m, □ >15 m							
WIT	WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 40						
SEC'	Depth(s) Groundwater Encountered (1)						
▎┌┐	Pump test data: Well water wasft. after						
EST. YIELDgpm. Well water wasft. after							oing gpm
W E Bore Hole Diameter !!!							t.
	WELL WATER TO BE USED AS: Public water supply Geothermal Injection well Domestic Feedlot Oil field water supply Dewatering Other (Specify below)						
57	SW - SE -						
	Was a chemical/bacteriological sample submitted to Department? Yes V No						
S If yes, mo/day/yr sample was submitted							
water weit distincted: [2] 1es [10]							
5 TYPE OF CASING USED: Steel V PVC Other							
Casing diameter 5 in to 30 ft. Diameter in to ft. Diameter in to ft. Diameter in to ft.							
Casing height above land surface. 16 in., Weight 160 lbs./ft., Wall thickness or gauge No214							
TYPE OF SCREEN OR PERFORATION MATERIAL: Steel Stainless Steel PVC Other (Specify)							
Brass Galvanized Steel None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE:							
☐ Continuous slot ☐ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole) ☐ Louvered shutter ☐ Key punched ☐ Wire wrapped ☑ Saw cut ☐ Other (specify)							
SCREEN-PERFORATED INTERVALS: From							
From							
GRAVEL PACK INTERVALS: From 40 ft. to 15 ft., From ft. to ft. From ft. to ft., From ft. to ft.							
6 GROUT MATERIAL: Neat cement Cement grout 7 Bentonite Other							
Grout Intervals: From .15 ft. to .0 ft., From ft. to ft., From ft. to ft.							
What is the nearest source of possible contamination:							
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well							
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well							
FROM	TO TO	n wellLITHOLOG		FROM			GGING INTERVALS
0	2	Top soil			Line. De	- (John.) <u>VI</u> 11.00	OHO MILKYALS
2	5	Brown sandy clay					
5	40	Medium sand and grave	el			***	
				 			
						,	
				-			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☐ constructed, ☐ reconstructed, or ☐ plugged							
under my jurisdiction and was completed on (mo/day/year) 6-29-2011 and this record is true to the best of my knowledge and belief							
Kansas Water Well Contractor's License No. 134 This Water Well Record was completed on (mo/day/year) 7-7-2011							
under the business name of Rosencrantz-Bemis Ent. by (signature) Lucia Dalla Dalla Benis Ent. INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies							
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.							
Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include <u>fee</u> of \$5.00 for each <u>constructed</u> well. Visit us at http://www.kdheks.gov/waterwell/index.html .							
KSA 82a-1212 Check: ✓ White Copy, ☐ Blue Copy, ☐ Pink Copy							