WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

County Fraction Range number	+
2. Distance and direction from nearest town or city: Street address of well location if in city: Street address of well location if in city: Sketch map: Sketch map: Sketch map: Sketch map: Sketch map: Sketch map: 6. Bore hole dia.	+
Street address of well location if in city: Sterling, Kansas 67579 A. Locate with "X" in section below: Sketch map: Sk	+
Sketch map: 6. Bore hole dia. 2 in. Completion date 4/30 Well depth 50 ft. 7. Cable tool Rotary Driven Dug Hollow rod Jetted Bored X Reverse rot 8. Use: Domestic Public supply Industry X Irrigation Air conditioning Stock Lawn Oil field water Other 9. Casing: Material Trans Histor: Above or below Threaded Welded Surface RMP PVC Weight 30 lbs./ Dia. 10n. to 1t. depth Wall Thickness: inches or Dia. 10. Screen: Manufacturer's name Johnson	+
4. Locate with "X" in section below: Sketch map: Sketch map: Sketch map: Sketch map: 6. Bore hole dia. 2. in. Completion date 24/30 Well depth 50 ft. 7Cable toolRotaryDrivenDug Hollow rodJettedBoredX Reverse rot 8. Use:DomesticPublic supplyIndustry X IrrigationAir conditioningStock LawnOil field waterOther 9. Casing: Material Trans thight: Above or below ThreadedWeldedISurfaceBRMPPVCWeightAIDIbs./ DiaIon. toOft. depth Wall Thickness: inches or DiaLon. toOft. depth lyage No3/16 10. Screen: Manufacturer's name	+
Well depth 50 ft. 7Cable toolRotaryDrivenDugHollow rodJettedBored _X Reverse rot 8. Use:DomesticPublic supplyIndustryX IrrigationAir conditioningStockLawnOil field waterOther 9. Casing: Material Trans Height: Above or below ThreadedWeldedSurfaceRMPPVCWeightBos./ DiaLon. toOft. depth Wall Thickness: inches or DiaLon. toOft. depth lyage No3/16 10. Screen: Manufacturer's name	+
7Cable toolRotaryDrivenDugHollow rodJettedBoredX Reverse rot 8. Use:DomesticPublic supplyIndustryX IrrigationAir conditioningStockLawnOil field waterOther 9. Casing: Material Trans thight: Above or below ThreadedWeldedSurface RMPPVCWeight30Ibs./ Dia1 fn. toft. depth Wall Thickness: inches or DiaLawnOil field waterOther 5. Type and color of material FromTo 10. Screen: Manufacturer's name	ry
Hollow rodJettedBored _X Reverse rot 8. Use:DomesticPublic supplyIndustry	ry
8. Use:DomesticPublic supplyIndustry	гу
X Irrigation _ Air conditioning _ Stock Lawn _ Oil field water _ Other Sw SE - SW - SW	
9. Casing: Material Trans Height: Above or below Threaded Welded Surface Threaded Welded Surface RMP PVC Weight 30 lbs./ Dia 16n. to ft. depth Wall Thickness: inches or Dia 16n. to ft. depth gage No 3/16 10. Screen: Manufacturer's name Johnson	
Threaded Welded Surface RMP PVC Weight 30 lbs./ Dia. 16n. to ft. depth Wall Thickness: inches or Dia. 16 in. to ft. depth gage No. 3/16 To 10. Screen: Manufacturer's name Johnson	
RMP PVC Weight 30 lbs./ Dia. 16n. to ft. depth Wall Thickness: inches or 5. Type and color of material From To 10. Screen: Manufacturer's name Johnson	.
Dia. 1 m. to ft. depth Wall Thickness: inches of Dia. 1 m. to ft. depth gage No. 3/16 5. Type and color of material From To Dia. 1 in. to ft. depth gage No. 3/16 10. Screen: Manufacturer's name Johnson	
10. Screen: Manufacturer's name	
Johnson	_
	-
Top soil 10 3 Type Sourch Dia. 16	-
Slot/gauze 3/16 Length 36	_
Fine sand & clay 3 6 Set between 86 ft. and 50	t.
ft. andft.	t.
Med. gravel 6 60 Gravel pack? Yesize range of material 3 1 4	=
11. Static water level: mo./day/ 9 ft. below land surface Date 4-30-7	}
	-
12. Pumping level below land surfaces: 15. ft. after hrs. pumping g.p.,	
ft. after hrs. pumping g.p.	
Estimated maximum yieldg.p.	
13. Water sample submitted: mo./day/	۲.
Yes X No Date	
14. Well head completion:	
Pitless adapter Inches above grade	┨.
15. Well grouted? <u>Yes</u> With: Neat cement Bentonite X Concre	اا
Depth: From ft. to _\O ft.	176
16. Negrest source of possible contamination:	┦ +
16. Nearest source of possible contamination: ft Direction to the perfect of the perfect	Δ
Well disinfected upon completion? Yes	<u>√</u>
17. Pump: Manufacturer's pame Board	~
Manufacturer's name Model number 5 4 HP 10 Volts 16	5 Î
Length of drop pipe 30 ft. capacity 600g.p.r.	
Туре:	_
Submersible Turbine	۱ ا
(Use a second sheet if needed) Jet Reciprocating Centrifugal Other	× 1
8. Elevation: 19. Remarks: 20. Water well contractor's certification:	↓ "⊢
D. FLEVOTION: 1.7. REMOTES!	
	'
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.	
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.	<u> </u>
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Topography:	1/4 1/
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Topography: Rosencrantz-Bemis Ent. Inc. 13	1/4 1/4 q