


1 LOCATION OF WATER WELL: County: Rice Fraction: NE 1/4 NE 1/4 NE 1/4 Section Number: 13 Township Number: T 21 S Range Number: R 9 E (W)

Distance and direction from nearest town or city street address of well if located within city?
1 mi. N, 2 1/2 W of Sterling

2 WATER WELL OWNER: Harvey Axtell
 RR#, St. Address, Box #: 2105 13th Rd
 City, State, ZIP Code: Sterling, KS 67579
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 49 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1. 8 ft. 2. 14 ft. 3. 25 ft.
 WELL'S STATIC WATER LEVEL 8 ft. below land surface measured on mo/day/yr 1-3-97
 Pump test data: Well water was 14 ft. after 2 hours pumping 25 gpm
 Est. Yield 25 gpm: Well water was 14 ft. after 2 hours pumping 25 gpm
 Bore Hole Diameter: 8 in. to 6.2 ft., and 6.2 in. to 6.2 ft.
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: X Glued Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded
 Blank casing diameter 5 in. to 39 ft., Dia 5 in. to 39 ft., Dia 5 in. to 39 ft.
 Casing height above land surface 12 in., weight 2.29 lbs./ft. Wall thickness or gauge No. 160
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 39 ft. to 49 ft., From 39 ft. to 49 ft., From 39 ft. to 49 ft.
 GRAVEL PACK INTERVALS: From 23 ft. to 31 ft., From 36 ft. to 62 ft., From 36 ft. to 62 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 3 ft. to 23 ft., From 31 ft. to 36 ft., From 36 ft. to 62 ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? NE How many feet? 60

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	8	Sandy silt			
8	32	Sand + Gravel			
32	36	Sandy Br Clay			
36	55	Sand + Gravel			
55	62	Br Clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-3-97 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 447 This Water Well Record was completed on (mo/day/yr) 1-9-97 under the business name of Miller Drilling by (signature) E. Mills

OFFICE USE ONLY