

1 LOCATION OF WATER WELL: County: Rice	Fraction NE ¼ SW ¼ NW ¼	Section Number 14	Township Number T 21 S	Range Number R 9 E/W
---	----------------------------	----------------------	---------------------------	-------------------------

Distance and direction from nearest town or city street address of well if located within city?
Approximately 1 1/4 miles east and 1 1/4 miles south of Alden

2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code	Jomax Construction Co., Inc. South Hwy 281 Great Bend, KS 67530	Temporary Permit Board of Agriculture, Division of Water Resources Application Number: 980277
---	---	---

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 30 ft. ELEVATION:
--	--

Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL 3 ft. below land surface measured on mo/day/yr 11-19-98

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter in. to ft., and in. to ft.

WELL WATER TO BE USED AS:

5 Public water supply	8 Air conditioning	11 Injection well
1 Domestic was	3 Feedlot	6 Oil field water supply
9 Dewatering	12 Other (Specify below)	
2 Irrigation	4 Industrial	7 Lawn and garden only
10 Monitoring well		

Was a chemical/bacteriological sample submitted to Department? Yes No ; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter 16 in. to ft. Dia			Threaded
Casing height above land surface All casing was pulled out			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify) NA
SCREEN-PERFORATED INTERVALS:	From 999 ft. to 999 ft.		
GRAVEL PACK INTERVALS:	From ft. to ft.		

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other Sand and clay
Grout Intervals:	From ft. to ft.	From ft. to ft.	From ft. to ft.	From 30 ft. to 0 ft.
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage
				13 Insecticide storage
				14 Abandoned water well
				15 Oil well/Gas well
				16 Other (specify below)
				None known
Direction from well?	How many feet?			

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
		This well was used to lower the water level from 3 feet to approximately 12 feet below surface. After a new 24" pipeline was installed under an existing large pipeline, the pump was removed. The well abandonment as follows:			
		1. Well was chlorinated.			
		2. The entire 16" x 30' long casing was pulled out. Because of the high water table and very loose gravel, the original 24" borehole collapsed immediately to approximately 4 feet below ground.			
		3. The large bell hole was filled with topsoil from 4 feet to surface.			
		Summary: The geological condition after the casing was removed remains the same as pre-existing condition.			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-19-98 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 185 This Water Well Record was completed on (mo/day/yr) 11-28-98 under the business name of Clarke Well & Equipment, Inc. by (signature)
