WATER WELL RECORD		Form W	WC-5	Division of Water Resources App. No.			
	1 LOCATION OF WATER WELL: County: Rice		Fraction 1/4 SE 1/4 SE	1/4 NW 1/4	Section Number Township No. Range Numb	er E ☑ W	
Stre	Street/Rural Address of Well Location; if unknown, distance & direction				Global Positioning System (GPS) information:		
fron	from nearest town or intersection: If at owner's address, check here .				Latitude: (in decimal degrees)		
21	2 1/2 South, 3/4 West of Alden			Longitude: (in decimal degrees)			
					Elevation:		
2 WA	TER W	ELL OWNER: Carmen	Schmidt		Datum: ☐ WGS 84, ☐ NAD 83, ☐ NAD 27 Collection Method:		
RR#, Street Address, Box #: P.O. Box 47					GPS unit (Make/Model:		
City	y, State, Z	ZID C 1	end, Ks. 67530		☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land	Survey	
					Est. Accuracy:	5 m	
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 45							
	TION BO	"IN 4 DEPTH OF C		Δ			
SEC	N N	WELL'S CLATI	ft. (2) ft. (3)	IL.			
l	Pump test data: Well water was				ft. after hours pumping	onm	
EST. YIELD. NA			Agpm. Well water	r was	ft. after hours pumping	gpm	
W E Bore Hole Diamet			eter 10in. to .:	45 1	ft., andft.	Or	
SW SE							
☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well Stock							
Was a chemical/bacteriological sample submitted to Department? ☐ Yes ☑ No If yes, mo/day/yr sample was submitted							
Water well disinfected? ✓ Yes ☐ No							
5 TYPE OF CASING USED: Steel V PVC Other							
CASING JOINTS: Glued Clamped Welded Threaded Casing diameter .5							
Casing height above land surface. 18 in., Weight SDR-26 lbs./ft., Wall thickness or gauge No.							
TYPE OF SCREEN OR PERFORATION MATERIAL:							
☐ Steel ☐ Stainless Steel							
Brass Galvanized Steel None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE: Continuous slot Gauze wrapped Torch cut Drilled holes None (open hole)							
☐ Continuous slot ☐ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole) ☐ Louvered shutter ☐ Key punched ☐ Wire wrapped ☑ Saw cut ☐ Other (specify)							
SCREEN-PERFORATED INTERVALS: From							
From							
GRAVEL PACK INTERVALS: From							
From ft. to ft., From ft. to ft.							
6 GROUT MATERIAL: Neat cement Cement grout Denotite Other Grout Intervals: From ft. to ft., From 20 ft. to ft., From ft. to ft.							
What is the nearest source of possible contamination:							
Septic tank							
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well							
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well None							
		n well			from well		
FROM 0	TO 3	LITHOLOG	IC LOG_	FROM	TO LITHO. LOG (cont.) or PLUGGING INTE	RVALS	
3	6	Sandy top soil				w.u.	
6	31	Sandy tan clay Sand & gravel-clean,me	nd coareo				
31	45	Sand & gravel-deart, me	u,coarse				
	1	Cana a gravor ornan				*	
	1						
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ✓ constructed, ☐ reconstructed, or ☐ plugged							
under my jurisdiction and was completed on (mo/day/year) .4/26/12 and this record is true to the best of my knowledge and belief.							
Kansas Water Well Contractor's License No. 134 This Water Well Record was completed on (mo/day/year) .5/21/12							
under the business name of Rosencrantz-Bemis by (signature) Some Colors INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies							
(white, blue, pink) to Kansas Depar truent of Health and E nvironment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 666 12-1367.							
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Vi sit us at							
http://www.kdheks.gov/waterwell/index.html. KSA 82a-1212 Check: White Copy, Deline Copy							
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy							