WATER WELL RECORD	Form WWC-5		er Resources App. No		
1 LOCATION OF WATER WELL:	Fraction	Section Number		Range Number	
County: Rice Street/Rural Address of Well Location;	1/4 NW 1/4 SE 1/4 SV		T 21 S g System (GPS) int	R 9 DE W	
from nearest town or intersection: If at		(in decimal degrees)			
2 3/4 South, 1 West of Alden		- 1	Longitude: (in decimal degrees)		
2 0/4 00001, 1 11000 01/110011		Elevation:	Elevation:		
2 WATER WELL OWNER: Mark Engelland		Datum: WGS 8	Datum: WGS 84, NAD 83, NAD 27		
RR#, Street Address, Box #: 1945 17th Road		Collection Method:	GPS unit (Make/Model)		
City, State, ZIP Code : Sterling, KS 67579		☐ Digital Map/Pl	☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey		
Est. Accuracy: [] <3 m, [] 3-5 m, [] 5-15 m					
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF	COMPLETED WELL 60	ft.			
				3) ft.	
N WELL'S STAT	WELL 5 STATIC WATER EL VILL				
Pump test data: Well water wasft. after					
W -NWNE EST. YIELD. N/Agpm. Well water was					
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well					
SW SF Domestic Feedlot Oil field water supply Dewatering Other (Specify below)					
Irrigation Industrial Domestic-lawn & garden Monitoring well 9.00%					
Was a chemical/bacteriological sample submitted to Department? ☐ Yes ☑ No					
S If yes, mo/day/yr sample was submitted					
water well disinfected: [2] Tes [170					
5 TYPE OF CASING USED: Steel PVC Other					
CASING JOINTS: Glued Clamped Welded Threaded Casing diameter 5 in to .60 ft., Diameter in to ft., Diameter in to ft.					
Casing height above land surface. 18 in., Weight SDR-26 lbs./ft., Wall thickness or gauge No.					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
Steel Stainless Steel PVC Other (Specify)					
☐ Brass ☐ Galvanized Steel ☐ None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:					
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)					
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)					
SCREEN-PERFORATED INTERVALS: From					
GRAVEL PACK INTERVALS: From 60 ft. to 20 ft., From ft. to ft.					
From					
6 GROUT MATERIAL: Neat cement Cement grout Denotite Other Other Grout Intervals: From ft. to ft., From 20 ft., From					
Grout Intervals: From ft. to ft., From .29 ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination: Septic tank Livestock pens Insecticide storage Other (specify below)					
Sewer lines					
☐ Watertight sewer lines ☐ Scepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well ☐ Pumping unit ☐ Direction from well Northwest ☐ Distance from well .250ft					
Direction from well Northwest FROM TO LITHOLOG				GGING INTERVALS	
0 4 Top soil	ic Lod rke	W TO LITTO. I	COU (COIII.) OI 1 LO	OGING INTERVALS	
4 18 Tan clay				7	
18 32 Sandy clay & fine sand	1				
32 60 Sand & gravel- med					
			royan yan katan kirin ya		
			· · · · · · · · · · · · · · · · · · ·		
				to the second se	
			· · · · · · · · · · · · · · · · · · ·		
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ✓ constructed, ☐ reconstructed, or ☐ plugged					
under my jurisdiction and was completed on (mo/day/year) .5-8-13 and this record is true to the best of my knowledge and belief.					
Kansas Water Well Contractor's License No. 134. This Water Well Record was completed on (mo/day/year) 6-18-13.					
under the business name of Rosencrantz-Bemis by (signature) School Rosencrantz Bemis by (signature)					
(white, blue, pink) to Kansas Depar tment of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.					
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include <u>fee</u> of \$5.00 for each constructed well. Vi sit us at http://www.kdheks.gov/waterwell/index.html .					
KSA 82a-1212 Check: X White Copy, Blue Copy, Pink Copy					