WATER WELL RECORD		Form WV	Division of Water Resources App. No.					
1 LOCATI County:	ION OF WATER WELL: Rice	Fraction SW ¼ SE ¼ NE	1/4 SW 1/4		n Number 30	Township No. T 21 S	Range Number R 9 □E ☑W	
from near	Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here				Global Positioning System (GPS) information: Latitude: .38,1921.11			
RR#, Str	eet Address, Box #: 745 Ave	d Cattle Company s. X (s 67512		Collection Method: ☐ GPS unit (Make/Model: Topcon GB500/GR-5 ☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m				
A DEPTH OF COMPLETED WELL 28.5 ft.								
5 TYPE OF CASING USED: ☐ Steel ☑ PVC ☐ Other CASING JOINTS: ☐ Glued ☐ Clamped ☐ Welded ☑ Threaded Casing diameter .2. ☐ in. to .28.5. ft., Diameter in. to ft., Diameter in. to ft. ☐ ft., Diameter in. to ft. Casing height above land surface .4. ☐ in., Weight Ibs./ft., Wall thickness or gauge No. ☐ Steel ☐ Stainless or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: ☐ Other (Specify) ☐ Brass ☐ Galvanized Steel ☐ None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: ☐ Other (Specify) ☐ Continuous slot ☑ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole) ☐ Louvered shutter ☐ Key punched ☐ Wire wrapped ☐ Saw cut ☐ Other (specify) SCREEN-PERFORATED INTERVALS: From 18.5 ft. to 28.5 ft., From ft. to ft. From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From ft. to ft., From ft. to ft.								
6 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout ☑ Bentonite ☐ Other ☐								
	TO LITHOLOG	GIC LOG	FROM	ТО			UGGING INTERVALS	
0' 4'	Brown Sand			****				
4' 15' 28								

		. 2 . 21						
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was \(\bigcup \) constructed, \(\bigcup \) reconstructed, or \(\bigcup \) plugged under my jurisdiction and was completed on \(\bigcup \) moday/year \(\) 3/11/14								
http://www.kdheks.gov/waterwell/index.html								