

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Harvey		North 1/4 Center 1/4 SE 1/4	9	T 22 S	R 1 W
Distance and direction from nearest town or city street address of well if located within city? Well located in the city of Hesston, KS. 737 Lewis					
2 WATER WELL OWNER: Don Milby		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box #: 737 Lewis		Application Number:			
City, State, ZIP Code: Hesston, KS. 67062					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 31 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 13 ft. 2. 11 ft. 3. 11-11-82 ft.			
		WELL'S STATIC WATER LEVEL 11 ft. below land surface measured on mo/day/yr 11-11-82			
		Pump test data: Well water was 14 ft. after 1 hours pumping 12 gpm			
		Est. Yield 25 gpm: Well water was 14 ft. after 1 hours pumping 12 gpm			
		Bore Hole Diameter 8 in. to 31 ft., and 12 in. to 31 ft.			
		WELL WATER TO BE USED AS:			
		<input checked="" type="checkbox"/> Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well			
		Was a chemical/bacteriological sample submitted to Department? Yes XX No XX ; If yes, mo/day/yr sample was submitted			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued XX Clamped XX			
1 Steel 3 RMP (SR)		5 Wrought iron 8 Concrete tile			
XX2 PVC 4 ABS		6 Asbestos-Cement 9 Other (specify below) Welded			
Blank casing diameter 5 in. to 21 ft., Dia		7 Fiberglass Threaded			
Casing height above land surface 12 in., weight 2.91 lbs./ft. Wall thickness or gauge No. .265					
TYPE OF SCREEN OR PERFORATION MATERIAL:		XX 7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)		11 Other (specify) XX			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot XX3 Mill slot 6 Wire wrapped 9 Drilled holes					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS:		From 21 ft. to 31 ft. From 31 ft. to 31 ft.			
GRAVEL PACK INTERVALS:		From 15 ft. to 31 ft. From 31 ft. to 31 ft.			
6 GROUT MATERIAL: XX1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 5 ft. to 15 ft. From 15 ft. to 15 ft.					
What is the nearest source of possible contamination:		150			
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well					
Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)					
Direction from well? north		How many feet? 150			
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	5	Top soil			
5	13	Red clay			
13	21	Medium white sand			
21	27	Green shale			
27	31	Red shale			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-11-82 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 138 This Water Well Record was completed on (mo/day/yr) 11-11-82 under the business name of Peterson Irrigation, Inc. by (signature) Mike Peterson					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					