


1 LOCATION OF WATER WELL: County: <u>Haryny</u>		Fraction $\frac{1}{4}$ <u>NW</u> $\textcircled{4}$	Section Number <u>10</u>	Township Number T <u>22</u> \textcircled{S}	Range Number R <u>1</u> \textcircled{EW}
Distance and direction from nearest town or city street address of well if located within city? <u>from Newton 5 M N from 24 ST and 4 M W</u>					
2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :		<u>Wibur prouty Heston Kansas</u> <u>RI</u> Board of Agriculture, Division of Water Resources Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL <u>98</u> ft. ELEVATION: <u>95</u> ft. Depth(s) Groundwater Encountered 1. _____ ft. 2. _____ ft. 3. _____ ft. WELL'S STATIC WATER LEVEL <u>20</u> ft. below land surface measured on mo/day/yr <u>Aug 20 1989</u> Pump test data: Well water was <u>60</u> ft. after <u>1</u> hours pumping <u>10</u> gpm Est. Yield <u>10</u> gpm: Well water was _____ ft. after _____ hours pumping _____ gpm Bore Hole Diameter <u>8</u> in. to _____ ft., and _____ in. to _____ ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes _____ No _____; If yes, mo/day/yr sample was submitted _____ Water Well Disinfected? Yes <u>X</u> No _____			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 2 PVC 4 ABS		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued _____ Clamped _____ 6 Asbestos-Cement 9 Other (specify below) Welded <u>X</u> 7 Fiberglass <u>SDR26</u> Threaded <u>3/16</u> Blank casing diameter <u>5</u> in. to <u>95</u> ft., Dia _____ in. to _____ ft., Dia _____ in. to _____ ft. Casing height above land surface <u>18</u> in., weight <u>200</u> lbs./ft. Wall thickness or gauge No. _____ TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) <u>SDR26</u> 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) _____ SCREEN-PERFORATED INTERVALS: From <u>20</u> ft. to <u>40</u> ft., From <u>60</u> ft. to <u>90</u> ft. From _____ ft. to _____ ft., From _____ ft. to _____ ft. GRAVEL PACK INTERVALS: From <u>10</u> ft. to <u>95</u> ft., From _____ ft. to _____ ft. From _____ ft. to _____ ft., From _____ ft. to _____ ft.			
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other		Grout Intervals: From <u>top 0</u> ft. to <u>10</u> ft., From _____ ft. to _____ ft., From _____ ft. to _____ ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage <u>400 none</u> Direction from well? <u>creek</u> <u>E</u> How many feet? <u>400</u>			
FROM TO LITHOLOGIC LOG		FROM TO PLUGGING INTERVALS			
<u>4 feet</u> <u>Top Soil</u>		<u>85</u> <u>90</u> <u>gravel ctye shale</u>			
<u>4</u>	<u>20</u>	<u>20</u>	<u>30</u>	<u>Blue Shale</u>	
<u>30</u>	<u>35</u>	<u>30</u>	<u>35</u>	<u>Sandy Blue Shale</u>	
<u>35</u>	<u>50</u>	<u>35</u>	<u>50</u>	<u>Blue Shale</u>	
<u>50</u>	<u>60</u>			<u>Rachup Blue Shale</u>	
<u>60</u>	<u>70</u>			<u>gravel ctye Shale</u>	
<u>70</u>	<u>75</u>			<u>limestone</u>	
<u>75</u>	<u>80</u>			<u>Sandy Shale Blue</u>	
<u>80</u>	<u>85</u>			<u>Blue Shale</u>	

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4

S well