			WATE	R WELL RECOP	RD Form V	WC-5 KSA 82a	1-1212			
1	N OF WAT		Fraction	\$4.3	115	Section Number			Range N	~
	arvey			<u>SW 14</u>			<u> </u>	S	R /	E/W)
		from nearest town	or city street a	ddress of well if	located within	city?				ļ
+	esston.	·					<u>-</u>			
WATER	WELL OW	NER: Marlin F	terbert							
RR#, St. A	ddress, Box	(# : 205W.	Hwysi				Board of Agr	iculture, Div	vision of Wate	er Resources
City, State,	ZIP Code	Hess	ton, Ks.	67062			Application N			
LOCATE AN "X" I	WELL'S LO	OCATION WITH 4	DEPTH OF C	OMPLETED WE	LL 25'.	ft. ELEVA	ATION:			
	1	, I w	ELL'S STATIC	WATER I EVEL	14 55	ft below land su	rface measured on m	o/day/yr	1-29-9	3
1 1	_ i	"								
-	- NW	NE					after		_	
1	!			9, 14 #					•	•
_₹ w ├-							and			π.
-	-	! W		O BE USED AS		ic water supply	8 Air conditioning		ection well	
ı -	_ sw	SE	1 Domestic	3 Feedlot			9 Dewatering			
	1		2 Irrigation	4 Industri			10 Monitoring well .			
↓ L	1	<u> </u>	as a chemical/	bacteriological sa	ample submitte	ed to Department? Y	'esNo. X	; If yes, m		nple was sub-
<u>-</u>		m	itted			Wa	ater Well Disinfected?		No	
TYPE O	F BLANK C	CASING USED:		5 Wrought iron	n 8	Concrete tile	CASING JOIN	TS: Glued .	Clam	ped
1 Ste	el	3 RMP (SR)		6 Asbestos-Ce	ement 9	Other (specify below	w)		1	
2 PV	<u> </u>	4 ABS		7 Fiberglass				Thread	ed.🗶	
Blank casir	ng diameter	2.3.75 in.	to . /.5	ft., Dia		.in. to	ft., Dia	in.	. <u>to</u> .	ft.
Casing heigh	ght above la	and surface.Flush	h Mount	.in., weight		Ibs.	/ft. Wall thickness or	gauge No.	206-13	5
		R PERFORATION I				7 PVĆ			Sch40	
1 Ste	el	3 Stainless s	teel	5 Fiberglass	_	8 RMP (SR)	11 Other	(specify) .		
2 Bra	ıss	4 Galvanized	steel	6 Concrete tile		9 ABS		used (oper		
SCREEN C	OR PERFOR	RATION OPENINGS	S ARE:	5	Gauzed wrap	pped	8 Saw cut		11 None (op	en hole)
	ntinuous slo				Wire wrappe	•	9 Drilled holes		(,
	uvered shutt		nunched	7	Torch cut		10 Other (specify)			
		ED INTERVALS:	From 2	5' ' _ғ	t to 15"	ft Fro	om	ft to		ft
OOMELIT		LD INTERVALO.	From	f	t to	ft Fro	om	ft to		ft
G	BAVEL PA	CK INTERVALS:	From 25	5. ′	t to		om			
	MANUEL IN	OK INTERVALO.	From		t to	# Erc	am.	ft to		ft
GROUT	MATERIAL	.: 1 Neat cer		2)Cement grout		Bentonite 4	Other			
Grout Inter			to 3	ft From		-# to ()	ft., From		ft to	ft
	nearest so	ource of possible	ntamination			(2)			andoned water	
		4 Lateral		7 Pit pr	inn.					
1 Septic tank 4 Lateral li 2 Sewer lines 5 Cess po							Fuel storage 15 Oil well/Gas well Fertilizer storage 16 Other (specify below)			
		er lines 6 Seepag		9 Feed	_		cticide storage .	10 0111	er (specify b	elow)
			le bit	9 Feed	yaru					
FROM	rom well'a	outhEast_	LITHOLOGIC	LOG		How ma	any feet? 60'	GGING IN	TERVALS	
A	.75	Concete	LITTOLOGIC	200		10 10	, 20			
775	43		0. 40			4 - 3 - 4 - 4				
ريّ 5	8.0	DRBrownic			antige.	MODILE				
9.5	16 15	4 um suis			0					
8.0	10.D	riea. Kea 130	nsuryce	ay w/ DK	Duchar	+				
		rottling a		,						
10.0	14.5	territory - M	IAY HOLL	edsardy	way w	caliche				
		HOLLIGAL, fu		grained so						
14.5	25,0			sitty sag						
		fine-med a				ر ا				
		fewinterni	ttent uni	سالميمك م	ٿي					
		<u> </u>								
7 CONTE	RACTOR'S	OR LANDOWNER'S	S CERTIFICAT	ION: This water	well was (1	constructed (2) rec	constructed, or (3) plu	inned undo	r my juriedio	tion and was
- CONTR	on (ma/da	/year) 1.2 - 29 - 9) CERTIFICAT	iois. Tilis water	Well Was (1					
					Makas Mari B		ord is true to the best			ellei. Nansas
		's License No. 5	•				on (mo/day/yr) .	Back		
		me of T.B.En			llurg	by (signa	7	THE REAL PROPERTY.		
							le the correct answers. Ser DWNER and retain one for		pies to Kansas	Department