

1 LOCATION OF WATER WELL		Fraction		Section Number		Township Number		Range Number	
County: HARVEY		NE 1/4 NE 1/4 SW 1/4		16		T 22 S		R 1 EW	
Distance and direction from nearest town or city? SAME				Street address of well if located within city? 206 S. Rupp-Hessien					

2 WATER WELL OWNER:		DELBERT FLAMING		Board of Agriculture, Division of Water Resources	
RR#, St. Address, Box # :		206 S. Rupp		Application Number:	
City, State, ZIP Code :		HESSON, KANSAS 67062			

3 DEPTH OF COMPLETED WELL		68 ft. Bore Hole Diameter		11 in. to 68 ft., and 11 in. to 68 ft.	
Well Water to be used as:		5 Public water supply		8 Air conditioning	
1 Domestic 3 Feedlot		6 Oil field water supply		9 Dewatering	
2 Irrigation 4 Industrial		7 Lawn and garden only		10 Observation well	
Well's static water level 9 ft. below land surface measured on 4 month 11 day 80 year					
Pump Test Data : Well water was 50 ft. after 2 hours pumping 14 gpm					
Est. Yield 10/15 gpm: Well water was 50 ft. after 2 hours pumping 14 gpm					

4 TYPE OF BLANK CASING USED:		5 Wrought iron		8 Concrete tile		Casing Joints: Glued X Clamped	
1 Steel		3 RMP (SR)		6 Asbestos-Cement		9 Other (specify below)	
2 PVC		4 ABS		7 Fiberglass		Welded	
						Threaded	
Blank casing dia 5" in. to 68 ft. Dia 18 in. to 2.83 lbs./ft. Wall thickness or gauge No 258							
Casing height above land surface 18 in. weight 2.83 lbs./ft. Wall thickness or gauge No 258							
TYPE OF SCREEN OR PERFORATION MATERIAL:		5 Fiberglass		8 RMP (SR)		10 Asbestos-cement	
1 Steel		3 Stainless steel		6 Concrete tile		9 ABS	
2 Brass		4 Galvanized steel		5 Gauzed wrapped		8 Saw cut	
Screen or Perforation Openings Are:		6 Wire wrapped		9 Drilled holes		11 None (open hole)	
1 Continuous slot		3 Mill slot		7 Torch cut		10 Other (specify)	
2 Louvered shutter		4 Key punched					
Screen-Perforation Dia 5" in. to 63 ft. Dia 15 ft. to 25 ft. Dia 10 ft. to 68 ft.							
Screen-Perforated Intervals: From 15 ft. to 25 ft. From 10 ft. to 68 ft.							
Gravel Pack Intervals: From 53 ft. to 63 ft. From 10 ft. to 68 ft.							

5 GROUT MATERIAL:		1 Neat cement		2 Cement grout		3 Bentonite		4 Other	
Grouted Intervals: From 0 ft. to 10 ft. From 10 ft. to 68 ft.									
What is the nearest source of possible contamination:		1 Septic tank		4 Cess pool		7 Sewage lagoon		10 Fuel storage	
2 Sewer lines		5 Seepage pit		8 Feed yard		11 Fertilizer storage		14 Abandoned water well	
3 Lateral lines		6 Pit privy		9 Livestock pens		12 Insecticide storage		15 Oil well/Gas well	
Direction from well South How many feet 25' ? Water Well Disinfected? Yes X No									
Was a chemical/bacteriological sample submitted to Department? Yes No If yes, date sample was submitted No month 29 day 80 year									
If Yes: Pump Manufacturer's name Paul's Inc. Model No. HP Volts No									
Depth of Pump Intake 4 ft. Pumps Capacity rated at 175 gal./min.									
Type of pump: 1 Submersible 2 Turbine 3 Jet 4 Centrifugal 5 Reciprocating 6 Other									

6 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on 4 month 11 day 80 year	
and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 175	
This Water Well Record was completed on 4 month 29 day 80 year under the business name of Paul's Inc. by (signature) Paul Bradburn	

7 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		FROM		TO		LITHOLOGIC LOG		FROM		TO		LITHOLOGIC LOG	
		0		2		Top Soil		63'		73'		FAULTED	
		2		6		5' CLAY		63		73		DRK-Blu SHALE	
		6		16		1st " " w/ ALK							
		16		19		med to coarse SAND							
		19		25		gr. SHALE							
		25		30		Heasht RL SHALE							
		30		35		GR-GRY SHALE							
35		40		" " to DRK SHALE									
40		53		DARK SHALE									
53		55		HARD wht (calc.) rock									
55		63		DRK-Blu SHALE									

ELEVATION:		Depth(s) Groundwater Encountered 1. 16' ft. 2. 53' ft. 3. 63' ft. 4. 80' ft.		(Use a second sheet if needed)	
------------	--	--	--	--------------------------------	--

OFFICE USE ONLY

T

R

EW

SEC

NE 1/4 NE 1/4 SW 1/4