11.004	OF 1441	CD MELL		H WELL RECC	JRD Form W	+				Niverbasi
	ON OF WAT		Fraction	<i>1/4/</i>	A	Section Number	1			Number
County:	H & ru	from nearest town			NE 1/4		J T 22	S	I R	/ <u>E</u> W
Distance a	na airection		-			•	0620	, 60	74	
<u> </u>					of He	55 ton -	OF JJ NU	1 60		
<b>-</b>	R WELL OW			an						_
-	Address, Box		35 NW	_				•	Division of V	Vater Resources
City, State,		: Hes	ston, K.	6706	1/0		Application			
3 LOCATE AN "X"	E WELL'S LO IN SECTION	OCATION WITH 4								
		1 D				<i></i> ft. 2				
₹ l	! !	<b>×</b>     w				. ft. below land sur				
	- NW	NE				<b>3</b> <i>9</i> ft. a				
1 [	1	Es	st. Yield	gpm: W	Vell water was	ft. a	ifter	. hours pu	mping	gpm
w kije		I B	ore Hole Diame	eter <b>9</b>	<b>ک.</b> in. to	T. <b>3</b>	and	in	. to	
≥ "	!	!   '  w	/ELL WATER T	O BE USED A			8 Air conditioning		Injection we	
ī l	- sw	SE	Domestic	3 Feedle		eld water supply				i
	1	1	2 Irrigation	4 Indust	trial 7 Lawn	and garden only	10 Monitoring wel	١		
1 L		_ I W	/as a chemical/t	pacteriological s	sample submitte	d to Department? Y	esNo	a; If yes	, mo/day/yr s	sample was sub-
<u>-</u>		m	itted			Wa	ter Well Disinfecte	ed? Yes	K No	)
5 TYPE C	OF BLANK C	CASING USED:		5 Wrought in	on 8 (	Concrete tile	CASING JO	INTS: Glue	d . 🗡 Cl	amped
1 Ste		3 RMP (SR)		6 Asbestos-C	Cement 9 (	Other (specify below	w)	Weld	ed	
<b>O</b> PV	/C	4 ABS	20	7 Fiberglass				Threa	aded	
Casing hei	ight above la	and surface/.	8	.in., weight		_	ft. Wall thickness	or gauge N	o /.4 .	2
TYPE OF	SCREEN O	R PERFORATION I	MATERIAL:		4	<b>∌</b> PVC	10 Asl	oestos-ceme	ent	ļ
1 Ste	eel	3 Stainless s	teel	5 Fiberglass		8 RMP (SR)	11 Oth	ner (specify)		
2 Bra	ass	4 Galvanized	steel	6 Concrete ti	ile	9 ABS	12 No	ne used (op	en hole)	
SCREEN (	OR PERFOR	RATION OPENINGS	S ARE:		5 Gauzed wrap	ped	8 Saw cut		11 None (	open hole)
1 Co	ontinuous slo	t 3 Mill	slot		6 Wire wrapped	I	9 Drilled holes			
2 Lo	uvered shut	ter 4 Key	punched		7 Torch cut		10 Other (specif	y)		
SCREEN-I	PERFORATI	ED INTERVALS:	From	.38	ft. to	<b>8</b> ft., Fro	m	ft. t	ю	
						ft., Fro				
(	GRAVEL PA	CK INTERVALS:	From	<i>2</i> .3	ft. to	<b>3</b> ft., Fro	m	ft. t	to	
			From		ft. to	ft., Fro	m	ft. t	to	ft.
6 GROUT	T MATERIAL			2 Cement gro	ut 💪		Other			
Grout Inter	rvals: Fro	m 3 ft.	. to <b> 2</b> . 3.	ft., Fron	n	. ft. to	ft., From		ft. to	
What is th	e nearest so	ource of possible co	ontamination:				stock pens		bandoned v	
Septic tank 4 Lateral lines			lines	7 Pit ș	privy	11 Fuel	11 Fuel storage 15 Oil well/Ga			well
2 Sewer lines 5 Cess pool				8 Sew	vage lagoon	12 Fertil	12 Fertilizer storage 16 Other (specify below)			
3 W	atertight sew	er lines 6 Seepag	je pit	9 Fee	dyard	13 Insec	cticide storage			
Direction f	from well?	$\omega_{-}$				How ma	iny feet? / 0			
FROM	то		LITHOLOGIC	LOG	FR	ом то	P	LUGGING I	NTERVALS	
	28	Br Clay	•							
28	34	Br Clay F Sand	)		100 100			E14 1-2-1-1-1		
34	48	C Sand + Yellowish	Sm Grac	12/						78.45
48	53	Yellowish	Br C/a							
		-								70°77 We' i
				1						
								TR Considerate addition		
			7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7							1 100 70 12
		· · · · · · · · · · · · · · · · · · ·								
7 00:-	DA0707:0	00.141001	000000000000000000000000000000000000000	ON				-1 - :		41-41
		OR LANDOWNER'S	S CERTIFICATI							
	on (mo/day	•	7-92			and this reco				d belief. Kansas
l .					Water Well Rec	ord was completed	-	0. d.	7. d	
	business na		Ver Dri			by (signa		mila	•	
		ypewriter or ball point pe				blanks, underline or circ d one to WATER WELL (				sas Department