

Harvey WATER WELL RECORD Form WWC-5 KSA 82a-1212 8-18-88 SB

1 LOCATION OF WATER WELL: Fraction $\frac{1}{4}$ NW $\frac{1}{4}$ NW Section Number 225 Township Number T 2622S Range Number R 1 E/W

County: Harvey Distance and direction from nearest town or city street address of well if located within city? N² W² 1/2 mi. on 81 2 1/2 mi

2 WATER WELL OWNER: Kansas crop service inc RR#, St. Address, Box #: City, State, ZIP Code: Whitewater Kansas 67154 Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 67 ft. ELEVATION: WELL'S STATIC WATER LEVEL: 22 ft. below land surface measured on mo/day/yr Mar 21 1985 Pump test data: Well water was 30 ft. after 1 hours pumping 15 gpm Est. Yield 15 gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 10 in. to 40 ft. and 8 in. to 6.7 ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded X Threaded SDR 26 Blank casing diameter 5 in. to 6.7 ft. Dia. in. to ft. Dia. in. to ft. Casing height above land surface 18 in., weight 200 lbs./ft. Wall thickness or gauge No. 3/16 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 30 ft. to 60 ft. From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From 10 ft. to 6.7 ft. From ft. to ft. From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From top ft. to 10 ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? 250 feet NW How many feet?

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) Mar 22 1986 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 221 This Water Well Record was completed on (mo/day/yr) Mar 23 1986 under the business name of Frank Bueckle by (signature) Frank Bueckle

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
top	3	top soil			
3	20	Brown clay			
20	30	Sand clay Blue			
30	40	White			
40	45	Blue clay			
45	50	Blue shale			
50	55	Cracking Blue shale			
55	67	Blue shale			