60 82 <b>WATER W</b>		RWD 3-06 Shallow ECORD	Form WWC-	5	Division	of Water	Resources; App. No.		
1 LOCATIO		VATER WELL:	Fraction SW 1/4 NW 1/4 S	SW 1/4	Section N		Township Number	Range Number R 1 E W	
Distance and direction from nearest town or city street address of well if located within city? Approximately 3/4 mile south and 3 miles west of Hesston.						Global Positioning Systems (decimal degrees, min. of 4 digits)  Latitude: 38.120584  Longitude: -97.481883			
2 WATER WELL OWNER: Harvey County RWD #1 RR#, St. Address, Box # : 107 N. Walnut P.O. Box 124 Peabody, KS 66866					Elevation: Unknown Datum: NAD 83				
							Method: WAAS GF	'S Unit	
S LOCATE LOCATION WITH AN SECTION NNW WSW	ON V''X'' IN V BOX:	Depth(s) Groundwater WELL'S STATIC WA	Encountered (1) TER LEVEL Not che : Well water was Note: : Well water was E USED AS: 5 Pul Feedlot 6 Oil fie	ecked for the checked of the checked	ft. below laned ft. after ft. after supply supply & garden)	d surface  8 Air c  9 Dews	measured on mo/da hours pumping hours pumping onditioning 11 atering 12	y/yrgpmgpm finjection well Other (Specify below) Observation Well	
S		Sample was submitted		Water	well disinf	fected?	Yes No	/	
1 Steel 2 PVC Blank casing Casing heigh TYPE OF SC	3 F 4 A diameter t above la EREEN O	IG USED: 5 Wrought RMP (SR) 6 Asbestos	Iron 8 Con -Cement 9 Oth s ft., Diameter 2 ( in., weight 70 PVC RIAL: glass 7 PVC	crete tile er (speci PVC) 3.65 steel	fy below) in. to 18 lbs./ft. Wa	CASING 5 ft., all thick	JOINTS: Glued  Welded  Threade  Diameter ness or gauge No.  11 Other (Specify)	Clamped  d ✓ in. to ft154 (both)	
SCREEN OR 1 Con	PERFO	RATION OPENINGS ARE of (3) Mill slot 5	: Gauzed wrapped 7	Forch cut	9 Dri	illed holes	11 None (open ho	ole)	
2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut SCREEN-PERFORATED INTERVALS: From 15 ft. to 25						er (Special From	ft. to	ft.	
SCREEN-PERFORATED INTERVALS: From         15         ft. to         25           From         ft. to         GRAVEL PACK INTERVALS: From         10         ft. to         30           From         ft. to         ft. to         30 <td>From From</td> <td>ft. to</td> <td>ft.</td>						From From	ft. to	ft.	
6 GROUT M	1ATERI	AL: 1 Neat Cement 2 (	Cement grout 3 Ben	tonite	4 Other		Bentonite Hole	plug	
Grout Interv	als: earest sour c	From 0 ft. to	ft., From	) Livesto	ft. to ck pens	ft 13 Insec 14 Abar	., From4 cticide Storage	ft. to 10 ft.  16 Other (specify	
		LITHOLOGICA O		low man			PLUGGING INT	EDVALC	
FROM T	O 1.5 T	LITHOLOGIC LOO	J	FROM	TO		FLOGGING INT	EKYALS	
1.5	12 C	lay, brown, silty and soft							
12		lay, gray, sandy							
15 25		and, tan, fine to coarse lay, gray, green, brown, s	soft						
Kansas Water	Well Con	OR LANDOWNER'S CER d was completed on (mo/day/y tractor's License No. 18 e of Clarke Well & Equipm ewriter or ball point pen. PLEASE A	This Water	Well Reco	ord was com	pleted on	(mo/day/year)	6-12-06	

copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.