


LOCATION OF WATER WELL: County: Stafford	Fraction NW 1/4 SW 1/4 NW 1/4	Section Number 17	Township Number T 22 S	Range Number R 11W E/W
--	---	-----------------------------	----------------------------------	----------------------------------

Distance and direction from nearest town or city street address of well if located within city?

5 E, 2-3/4 N of Hudson, Kansas

WATER WELL OWNER: Norman Klepper	H-30 Drilling, Inc.	Klepper NW 2
R#, St. Address, Box # Ellinwood, KS	251 N. Water, Suite 10	Board of Agriculture, Division of Water Resources
City, State, ZIP Code 67526	Wichita, KS 67202	Application Number: T88-356

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

DEPTH OF COMPLETED WELL: **80** ft. ELEVATION: **Unknown**Depth(s) Groundwater Encountered 1. **43** ft. 2. **43** ft. 3. **43** ft.WELL'S STATIC WATER LEVEL **43** ft. below land surface measured on mo/day/yr **7/5/88**Pump test data: Well water was **60** gpm: Well water was **80** ft. after **7** hours pumping **80** gpmEst. Yield **60** gpm: Well water was **80** ft. after **7** hours pumping **80** gpmBore Hole Diameter **8** in. to **80** ft., and **80** in. to **80** ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well

Was a chemical/bacteriological sample submitted to Department? Yes **X** No **X**; If yes, mo/day/yr sample was submittedWater Well Disinfected? Yes **X** No **X**TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued **X** Clamped **X**1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded **X**2 PVC 4 ABS 7 Fiberglass Threaded **X**Blank casing diameter **5** in. to **60** ft., Dia **5** in. to **60** ft., Dia **5** in. to **60** ft.Casing height above land surface **12** in., weight **2.8** lbs./ft. Wall thickness or gauge No. **Sch. 40**

TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement

1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)

2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes

2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From **60** ft. to **80** ft., From **60** ft. to **80** ft., From **60** ft. to **80** ft.From **60** ft. to **80** ft., From **60** ft. to **80** ft., From **60** ft. to **80** ft.GRAVEL PACK INTERVALS: From **20** ft. to **80** ft., From **20** ft. to **80** ft., From **20** ft. to **80** ft.From **20** ft. to **80** ft., From **20** ft. to **80** ft., From **20** ft. to **80** ft.

GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout intervals: From **0** ft. to **20** ft., From **0** ft. to **20** ft., From **0** ft. to **20** ft.

What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well

1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage

Direction from well? **South** How many feet? **60**

FROM TO LITHOLOGIC LOG FROM TO LITHOLOGIC LOG

80' **5** **Neat cement**