


PMW-2

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: STAFFORD	NW 1/4 NE 1/4 NE 1/4	32	T 22 S	R 12 E (N)

Distance and direction from nearest town or city street address of well if located within city?

SOUTH AVE., HUNSMAN, KANSAS

2 WATER WELL OWNER:	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # : City, State, ZIP Code :	Application Number:
COUNTRYSIDE SERVICE RR1, BOX 28, HUNSMAN, KS. 66545	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL	50 ft. ELEVATION:
	Depth(s) Groundwater Encountered 21.04 ft. 2 70 ft. 3 7/24/03 ft.	
	WELL'S STATIC WATER LEVEL 21.04 ft. below land surface measured on mo/day/yr	
	Pump test data: Well water was N/A ft. after 7/24/03 hours pumping 7/24/03 gpm	
	Est. Yield N/A gpm: Well water was N/A ft. after 7/24/03 hours pumping 7/24/03 gpm	
	WELL WATER TO BE USED AS:	
	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)	
	2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well	
	Was a chemical/bacteriological sample submitted to Department? Yes ☒ No ☒ If yes, mo/day/yr sample was submitted	
	Water Well Disinfected? Yes ☒ No ☒	

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued ☒ Clamped ☒
1 Steel	6 Asbestos-Cement	9 Other (specify below)	Welded ☒
2 PVC	7 Fiberglass		Threaded ☒
Blank casing diameter 2.375 in. to 15 ft., Dia			
Casing height above land surface FLUSH MOUNT in., weight			
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel	5 Fiberglass	10 Asbestos-Cement	
2 Brass	6 Concrete tile	8 RMP (SR)	
		9 ABS	
SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot	5 Guazed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter	6 Wire wrapped	9 Drilled holes	
	7 Torch cut	10 Other (specify)	
SCREEN-PERFORATED INTERVALS:			
From 30 ft. to 15 ft., From 15 ft. to 70 ft.			
GRAVEL PACK INTERVALS:			
From 30 ft. to 13 ft., From 13 ft. to 70 ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other CONCRETE
Grout intervals: From 13 ft. to 2.5 ft., From 2.5 ft. to 70 ft.				
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage (FURNACE)	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well? EAST			13 Insecticide storage	
			How many feet? 10	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	0.5	CONCRETE			
0.5	5.5	DRBN-OLIVE SILTY CLAY FIRM-FRIABLE FIRM, MOIST, MOD. UNDER			
5.5	9	BN SANDY CLAY, FRIABLE, MOIST, MOD. UNDER			
9	13	RED BN SANDY CLAY-CLAYEY SAND FINE-COARSE GRAINED, DEV. MOD. O			
13	16.5	OLIVE GN CLAYEY SAND, MOTTLED RED BN, FRIABLE-FIRM, DEV. MOD. O			
16.5	30	LT RED BN SILTY SAND, FINE-COARSE GRAINED, WET TO MOD. UNDER			
FLUSH MOUNT WELL COMPLETION APPROVED BY D. TAYLOR, KSHE-BOW					

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7/24/03 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 662 This Water Well Record was completed on (mo/day/yr) 7/24/03 under the business name of QUAN STATE SERVICES, INC. by (signature) [Signature]
--