

KRANKENBERG #1 WATER WELL RECORD Form WWC-5 KSA 82a-1212

LOCATION OF WATER WELL: Fraction C 5/8 1/4 SW 1/4 SW 1/4 Section Number 6 Township Number T 22 S Range Number R 12 E W

County: STAFFORD Distance and direction from nearest town or city street address of well if located within city? HUDSON 3 1/2 N 1 3/4 W NORTHSIDE.

WATER WELL OWNER: CRUDE RECOVERY G. KRANKENBERG, HUDSON, KS.

RR#, St. Address, Box #: 555 NORTH WOODLAWN Board of Agriculture, Division of Water Resources

City, State, ZIP Code: WICAITA, KS. 67208 Application Number: T84-934

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

DEPTH OF COMPLETED WELL: 90 ft. ELEVATION: 66 ft.

WELL'S STATIC WATER LEVEL: 20 ft. below land surface measured on mo/day/yr 12-3-84

Pump test data: Well water was 1 ft. after 12 hours pumping 12-3-84

Est. Yield: 12 gpm. Well water was 1 ft. after 12 hours pumping 12-3-84

Bore Hole Diameter: 7 1/8 in. to 9 in. ft., and in. to ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well

Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No

TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued XX Clamped

2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded

Blank casing diameter: 5 in. to 70 ft., Dia. in. to ft., Dia. in. to ft.

Casing height above land surface: 12 in., weight 2.65 lbs./ft. Wall thickness or gauge No. 214

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement

2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)

SCREEN OR PERFORATION OPENINGS ARE: 1/8 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes

2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 70 ft. to 90 ft., From ft. to ft.

GRAVEL PACK INTERVALS: From 60 ft. to 90 ft., From ft. to ft.

GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 0 ft. to 10 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well

1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage

Direction from well? How many feet?

FROM TO LITHOLOGIC LOG FROM TO LITHOLOGIC LOG

0 50 SAND & TOP SOIL

5 55 CLAY

55 65 SANDY CLAY

65 90 GRAVEL

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-3-84 and this record is true to the best of my knowledge and belief. Kansas

Water Well Contractor's License No. 389 This Water Well Record was completed on (mo/day/yr) 12-12-84

under the business name of PEISER WATER WELL SERV INC. by (signature) Richard J. Peiser

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

R

E

SEC.

6

5

1/4

SW

1/4

SW

1/4