

LOCATION OF WATER WELL:		Fraction	Pump Wires	RCA CATE	
County:	Township Number	Range Number			
Stafford	S 1 1/2 T SE 1/4 SE 1/4	9	T 22 S R 12 NW		
Distance and direction from nearest town or city street address of well if located within city? <u>1 E.- 3 N. Hudson, Ks.</u>					
WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :		Emphasis Oil Box 506 Russell, Ks. 67665			
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		Board of Agriculture, Division of Water Resources Application Number: T 89-284			
		DEPTH OF COMPLETED WELL.....110 ft. ELEVATION:ft. Depth(s) Groundwater Encountered 1.ft. 2.ft. 3.ft. WELL'S STATIC WATER LEVEL22.. ft. below land surface measured on mo/day/yr <u>6-23-89</u> . Pump test data: Well water wasft. after hours pumping gpm Est. Yield .NA.... gpm; Well water wasft. after hours pumping gpm Bore Hole Diameter. ...10...in. to ...110...ft., and.....in. toft. WELL WATER TO BE USED AS: <u>5 Public water supply</u> 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes.....No.. <u>X</u>; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes HTH No			
TYPE OF BLANK CASING USED:		CASING JOINTS: Glued <u>X</u> Clamped			
1 Steel 3 RMP (SR)		5 Wrought iron 8 Concrete tile Concrete tiled			
2 PVC 4 ABS		6 Asbestos-Cement 9 Other (specify below) Welded			
Blank casing diameter5...in. to ...90...ft., Diain. toft., Diain. toft.		7 Fiberglass Threaded			
Casing height above land surface18"...in., weight258 lbs./ft. Wall thickness or gauge No.					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel		8 RMP (SR) 11 Other (specify)			
2 Brass 4 Galvanized steel		9 ABS 12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot		9 Drilled holes			
2 Louvered shutter 4 Key punched		10 Other (specify)			
SCREEN-PERFORATED INTERVALS: From90...ft. to110...ft., Fromft. toft.					
GRAVEL PACK INTERVALS: From20...ft. to110...ft., Fromft. toft.					
GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout intervals: From0...ft. to20...ft., Fromft. toft., Fromft. toft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy		11 Fuel storage 15 Oil well/Gas well			
2 Sewer lines 5 Cess pool 8 Sewage lagoon		12 Fertilizer storage 16 Other (specify below)			
3 Watertight sewer lines 6 Seepage pit 9 Feedyard		13 Insecticide storage			
Direction from well? North West		How many feet? 60 ft.			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Sandy Top Soil			
3	9	Brown Clay			
9	17	Light Brown Clay			
17	23	Gray Clay			
23	34	Brown Clay			
34	38	Fine Sand			
38	77	Sand with Clay Mixed			
77	110	Sand & Gravel			
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>6/23/89</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>134</u> This Water Well Record was completed on (mo/day/yr) <u>6/29/89</u> Under the business name of Rosencrantz-Bemis by (signature) Fredia Bladen					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320. Telephone: 913-296-5514. Send one to WATER WELL OWNER and retain one for your records.					