


C. SPANGENBERG		WATER WELL RECORD		Form WWC-5	KSA 82a-1212
LOCATION OF WATER WELL:		Fraction	165' S	Section Number	10
County:	STAFFORD	NE 1/4 SW 1/4 NW 1/4		Township Number	T 22 S
Distance and direction from nearest town or city street address of well if located within city?		R 12 E			
HUDSON 3 1/2 N 1 1/4 E SOUTH SIDE.					
WATER WELL OWNER:		L.D. DRILLING INC.			
R#, St. Address, Box #:		RT. 1 BOX 183B			
City, State, ZIP Code:		GREAT BEND, KS 67530			
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		2... SPANGENBERG, HUDSON, KS			
		Board of Agriculture, Division of Water Resources			
		Application Number: T85-37			
DEPTH OF COMPLETED WELL: 100 ft.		ELEVATION: 1776 ft.			
WELL'S STATIC WATER LEVEL: 18 ft. below land surface measured on mo/day/yr 1-7-85					
Pump test data: Well water was 1 ft. after 1 hour pumping 1 gpm					
Est. Yield 1 gpm: Well water was 1 ft. after 1 hour pumping 1 gpm					
Bore Hole Diameter: 7 7/8 in. to 100 ft. and 1 in. to 100 ft.					
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well			
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)					
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well					
Was a chemical/bacteriological sample submitted to Department? Yes.....No.....; If yes, mo/day/yr sample was submitted		Water Well Disinfected? Yes No			
TYPE OF BLANK CASING USED:		CASING JOINTS: Glued by Clamped			
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded					
2 PVC 4 ABS 7 Fiberglass Threaded					
Blank casing diameter 5 in. to 80 ft. Dia. 1 in. to 100 ft. Dia.					
Casing height above land surface 12 in. weight 2.65 lbs./ft. Wall thickness or gauge No. 214					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE: 1/8		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 80 ft. to 100 ft. From 100 ft. to 100 ft.					
GRAVEL PACK INTERVALS: From 70 ft. to 100 ft. From 100 ft. to 100 ft.					
GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 0 ft. to 10 ft. From 10 ft. to 100 ft.					
What is the nearest source of possible contamination: NONE		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage					
Direction from well?		How many feet?			
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	4	TOP SOIL			
4	300	CLAY			
30	400	SANDY CLAY			
40	700	CLAY			
70	750	SANDY CLAY			
75	100	GRAVEL			
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-7-85 and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. 389 This Water Well Record was completed on (mo/day/yr) 1-15-85					
Under the business name of REISER WATER WELL SERV. INC. by (signature) Rudolph Reiser					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					