


LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Stafford		SW 1/4 NE 1/4 SE 1/4	10	T 22 S	R 12 E/W
Distance and direction from nearest town or city street address of well if located within city? 2 3/4 north 1 3/4 east of Hudson					
WATER WELL OWNER: Bob Siefkes		Slawson Drilling		Board of Agriculture, Division of Water Resources	
RR#, St. Address, Box #: Hudson, Ks.		Box 1409		Application Number: T83-157	
City, State, ZIP Code: Great Bend, Ks. 67530					
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		DEPTH OF COMPLETED WELL: 110 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 19 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 30 ft. below land surface measured on mo/day/yr 4-27-83			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield NA gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 11 in. to 110 ft., and in. to ft.			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well			
		Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes HTH No			
TYPE OF BLANK CASING USED:		5 Wrought iron 8 Concrete tile		CASING JOINTS: Glued X Clamped	
1 Steel 3 RMP (SR)		6 Asbestos-Cement 9 Other (specify below)		Welded	
2 PVC 4 ABS		7 Fiberglass		Threaded	
Blank casing diameter 5 in. to 90 ft., Dia. in. to ft., Dia. in. to ft.		Casing height above land surface 18 in., weight lbs./ft. Wall thickness or gauge No. .258			
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 90 ft. to 110 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 10 ft. to 110 ft., From ft. to ft.					
GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 0 ft. to 10 ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)					
Direction from well? west		How many feet? 80			
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	10 04	Sandy top soil			
10	60 01	Clay			
60	75 04	Sandy clay			
75	110 17	Sand and gravel			
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-27-83 and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. 134 This Water Well Record was completed on (mo/day/yr) 5-25-83					
Under the business name of Rosencrantz-Bemis Ent. by (signature) Lora Dodson					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

R

EW

SEC.

10

24

1E

1/4

SE

1/4

DP