

LOCATION OF WATER WELL:		Fraction	Township Number	Range Number	
County: STAFFORD		$\frac{1}{4}$ SW $\frac{1}{4}$ SE $\frac{1}{4}$ NE $\frac{1}{4}$	Section Number 10	T 22 S R 12 E	
Distance and direction from nearest town or city street address of well if located within city?					
HUDSON 2E 3 1/2 N WESTSIDE					
WATER WELL OWNER: L.D. DRILLING CO. INC.		L AHNERT ST. JOHN, KS.			
R#, St. Address, Box # BOX 183B ROUTE 1		Board of Agriculture, Division of Water Resources			
City, State, ZIP Code GREAT BEND, KS 67520		Application Number: T82-168			
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		DEPTH OF COMPLETED WELL: 9.5 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 7.0 ft. 2. .ft. 3. .ft.			
		WELL'S STATIC WATER LEVEL 16 ft. below land surface measured on mo/day/yr 3-26-82			
		Pump test data: Well water was .ft. after . hours pumping gpm			
		Est. Yield gpm: Well water was .ft. after . hours pumping gpm			
		Bore Hole Diameter 7.718 in. to 9.5 ft., and .in. to .ft.			
		WELL WATER TO BE USED AS:			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well			
		Was a chemical/bacteriological sample submitted to Department? Yes.....No.....; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No			
TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped Welded Threaded			
1 Steel 3 RMP (SR)		5 Wrought iron 8 Concrete tile			
2 PVC 4 ABS		6 Asbestos-Cement 9 Other (specify below)			
Blank casing diameter 5 in. to 7.5 ft., Dia		7 Fiberglass			
Casing height above land surface 12 in., weight 2.65 lbs./ft. Wall thickness or gauge No. 7.14					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass		8 RMP (SR)			
2 Brass 4 Galvanized steel 6 Concrete tile		9 ABS			
SCREEN OR PERFORATION OPENINGS ARE: 1/8		8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot		9 Drilled holes			
2 Louvered shutter 4 Key punched		10 Other (specify)			
SCREEN-PERFORATED INTERVALS:		From 7.5 ft. to 9.5 ft., From .ft. to .ft.			
GRAVEL PACK INTERVALS:		From 6.5 ft. to 9.5 ft., From .ft. to .ft.			
GROUT MATERIAL:		3 Bentonite 4 Other			
Grout Intervals: From 0 ft. to 10 ft., From .ft. to .ft.					
What is the nearest source of possible contamination: NONE		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines		11 Fuel storage 15 Oil well/Gas well			
2 Sewer lines 5 Cess pool		12 Fertilizer storage 16 Other (specify below)			
3 Watertight sewer lines 6 Seepage pit		13 Insecticide storage			
Direction from well?		How many feet?			
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	8	SANDY SOIL			
8	70	SANDY CLAY			
70	95	GRAVEL			
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-26-82 and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. 389 This Water Well Record was completed on (mo/day/yr) 4-5-82					
Under the business name of NELSEN WATER WELL SERV. INC. by (signature) [Signature]					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					