

HEYEN #3
WATER WELL RECORD Form WWC-5 KSA 82a-1212
LOCATION OF WATER WELL:
County: STAFFORD Fraction: NW 1/4 NW 1/4 SE 1/4 Section Number: 24 Township Number: T 22 S Range Number: R 12 E
Distance and direction from nearest town or city street address of well if located within city:
HUDSON 4E 1 1/2 M WESTSIDE
WATER WELL OWNER: L.D. DRILLING CO. INC.
RT 1 BOX 183B
City, State, ZIP Code: GREAT BEND, KS 67530
Board of Agriculture, Division of Water Resources
Application Number: 783-20
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:
[Section Box Diagram]
DEPTH OF COMPLETED WELL: 100 ft. ELEVATION: 45 ft.
WELL'S STATIC WATER LEVEL: 25 ft. below land surface measured on mo/day/yr: 1-4-83
Pump test data: Well water was 2 ft. after 1 hour pumping 1 gpm
Est. Yield: 778 gpm; Well water was 100 ft. after 1 hour pumping 1 gpm
Bore Hole Diameter: 7.78 in. to 100 ft., and 100 in. to 100 ft.
WELL WATER TO BE USED AS: 5 Public water supply, 8 Air conditioning, 11 Injection well, 12 Other (Specify below)
Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted
Water Well Disinfected? Yes No
TYPE OF BLANK CASING USED: 1 Steel, 3 RMP (SR), 5 Wrought iron, 8 Concrete tile, CASING JOINTS: Glued, Clamped
Blank casing diameter: 5 in. to 80 ft., Dia. 80 in. to 80 ft., Dia. 80 in. to 80 ft., Dia. 80 in. to 80 ft.
Casing height above land surface: 12 in., weight 2.65 lbs./ft. Wall thickness or gauge No. 2.14
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel, 3 Stainless steel, 5 Fiberglass, 8 RMP (SR), 10 Asbestos-cement, 11 Other (specify), 12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot, 3 Mill slot, 5 Gauzed wrapped, 8 Saw cut, 11 None (open hole)
SCREEN-PERFORATED INTERVALS: From 80 ft. to 100 ft., From 80 ft. to 100 ft., From 80 ft. to 100 ft., From 80 ft. to 100 ft.
GRAVEL PACK INTERVALS: From 70 ft. to 100 ft., From 70 ft. to 100 ft., From 70 ft. to 100 ft., From 70 ft. to 100 ft.
GROUT MATERIAL: 1 Neat cement, 2 Cement grout, 3 Bentonite, 4 Other
Grout intervals: From 0 ft. to 10 ft., From 0 ft. to 10 ft., From 0 ft. to 10 ft., From 0 ft. to 10 ft.
What is the nearest source of possible contamination: NONE
1 Septic tank, 4 Lateral lines, 7 Pit privy, 10 Livestock pens, 14 Abandoned water well
2 Sewer lines, 5 Cess pool, 8 Sewage lagoon, 11 Fuel storage, 15 Oil well/Gas well
3 Watertight sewer lines, 6 Seepage pit, 9 Feedyard, 12 Fertilizer storage, 16 Other (specify below)
Direction from well?
FROM TO LITHOLOGIC LOG FROM TO LITHOLOGIC LOG
0 15 SAND
15 45 SANDY CLAY
45 55 GRAVEL
55 80 CLAY
80 100 GRAVEL
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-4-83 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 389 This Water Well Record was completed on (mo/day/yr) 1-12-83 under the business name of REISER WATER WELL SERV. INC. by (signature)
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY
T 22
R 12
E W
NW 1/4
NW 1/4
SE 1/4