


LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number	
County: Stafford	NW 1/4 SW 1/4 ne 1/4	27	T 22 S	R 12 E/W	
Distance and direction from nearest town or city street address of well if located within city? 1/4 north 1 3/4 east of Hudson, Ks.					
WATER WELL OWNER: Lewis SSchiel WheatState Drilling IR#, St. Address, Box #: Hudson, Ks. Box 947 Board of Agriculture, Division of Water Resources City, State, ZIP Code: Pratt, Ks. 67124 Application Number: T84-264					
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		DEPTH OF COMPLETED WELL: 100 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 12 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 1.5 ft. below land surface measured on mo/day/yr 5-9-84 Pump test data: Well water was ft. after hours pumping gpm Est. Yield na gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 1.0 in. to 1.00 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes hth No			
TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: <u>Glued</u> Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) <u>Welded</u> <u>2 PVC</u> 4 ABS 7 Fiberglass Threaded Blank casing diameter 5 in. to 8.0 ft., Dia. in. to ft., Dia. in. to ft. Casing height above land surface 1.8 in., weight lbs./ft. Wall thickness or gauge No. .258 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 8.0 ft. to 1.00 ft., From ft. to ft. From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From 1.0 ft. to 1.00 ft., From ft. to ft. From ft. to ft., From ft. to ft. GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout intervals: From 0 ft. to 1.0 ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage Direction from well? west How many feet? 150					
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	Top soil			
2	12	Clay			
12	30	Sand and clay layers			
30	60	Sandy clay			
60	102	Sand and gravel			
102	106	clay			
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-9-84 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 134 This Water Well Record was completed on (mo/day/yr) 7-31-84 Under the business name of Rosencrantz-Bemis Ent. by (signature) Dora Dodson INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					