

LOCATION OF WATER WELL:		Fraction		Township Number		Range Number	
County: <u>Stafford</u>		<u>SW 1/4 NE 1/4 SE 1/4</u>		<u>29</u>		<u>T 22 S R 12 E/W</u>	
Distance and direction from nearest town or city street address of well if located within city?							
<u>View Street</u>							
WATER WELL OWNER:		Mike Hill		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box # :		Hudson, Ks. 67545		Application Number:			
City, State, ZIP Code :							
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 10.0 ft. ELEVATION:					
N W E S -- NW -- -- NE -- -- SW -- -- SE --		Depth(s) Groundwater Encountered 1. 19 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 23 ft. below land surface measured on mo/day/yr 8-3-83 Pump test data: Well water was ft. after hours pumping gpm Est. Yield NA gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 10 in. to 10.0 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes No. x; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes HTH No					
TYPE OF BLANK CASING USED:		5 Wrought iron		8 Concrete tile		CASING JOINTS: Glued x Clamped	
1 Steel		3 RMP (SR)		6 Asbestos-Cement		Welded	
2 PVC		4 ABS		7 Fiberglass		Threaded	
Blank casing diameter 5 in. to 8.0 ft. Dia		in. to ft. Dia		in. to ft. Dia		in. to ft. Dia	
Casing height above land surface 18 in. weight lbs./ft. Wall thickness or gauge No. 25.8							
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC		10 Asbestos-cement			
1 Steel		3 Stainless steel		8 RMP (SR)		11 Other (specify)	
2 Brass		4 Galvanized steel		9 ABS		12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped		8 Saw cut		11 None (open hole)	
1 Continuous slot		3 Mill slot		9 Drilled holes			
2 Louvered shutter		4 Key punched		10 Other (specify)			
SCREEN-PERFORATED INTERVALS:		From 8.0 ft. to 10.0 ft.		From ft. to ft.		From ft. to ft.	
GRAVEL PACK INTERVALS:		From 1.0 ft. to 10.0 ft.		From ft. to ft.		From ft. to ft.	
GROUT MATERIAL:		1 Neat cement		2 Cement grout		3 Bentonite	
Grout Intervals: From 0 ft. to 1.0 ft.		From ft. to ft.		From ft. to ft.		From ft. to ft.	
What is the nearest source of possible contamination:		1 Septic tank		4 Lateral lines		7 Pit privy	
2 Sewer lines		5 Cess pool		8 Sewage lagoon		9 Feedyard	
3 Watertight sewer lines		6 Seepage pit		10 Livestock pens		14 Abandoned water well	
				11 Fuel storage		15 Oil well/Gas well	
				12 Fertilizer storage		16 Other (specify below)	
				13 Insecticide storage			
Direction from well? east				How many feet? 90			
FROM TO LITHOLOGIC LOG		FROM TO LITHOLOGIC LOG		FROM TO LITHOLOGIC LOG		FROM TO LITHOLOGIC LOG	
0 5 Dark top soil							
5 37.01 Tan clay							
37 72.04 Tan sandy clay w/white broken rock							
72 78.13 Small gravel							
78 100.14 Medium gravel							
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-3-83 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 134 This Water Well Record was completed on (mo/day/yr) 9-14-83 under the business name of Rosencrantz-Bemis Ent. by (signature) Lora Dodson							
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.							