

LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number		
County: Stafford		SE 1/4 NE 1/4 SE 1/4	35	T 22 S	R 12W E/W		
Distance and direction from nearest town or city street address of well if located within city? 3 E, 3/4 S of Hudson, Kansas							
WATER WELL OWNER: Boyd McCune		Rains & Williamson		McCune No. 1			
IR#, St. Address, Box #: Stafford, Ks.		220 W Douglas		Board of Agriculture, Division of Water Resources			
City, State, ZIP Code: 67578		Wichita, Kansas 67202		Application Number: Unknown			
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		DEPTH OF COMPLETED WELL: 80 ft. ELEVATION: Unknown					
		Depth(s) Groundwater Encountered 1. 12 ft. 2. .ft. 3. .ft.					
		WELL'S STATIC WATER LEVEL: 12 ft. below land surface measured on mo/day/yr 2/11/84					
		Pump test data: Well water was .ft. after . hours pumping . gpm					
		Est. Yield 60 gpm: Well water was .ft. after . hours pumping . gpm					
		Bore Hole Diameter: 8 in. to 80 ft., and . in. to .ft.					
		WELL WATER TO BE USED AS:					
		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well					
		Was a chemical/bacteriological sample submitted to Department? Yes..... No; If yes, mo/day/yr sample was submitted					
		Water Well Disinfected? Yes No					
TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped					
1 Steel 3 RMP (SR)		5 Wrought iron 8 Concrete tile 9 Other (specify below)					
2 PVC 4 ABS		6 Asbestos-Cement 7 Fiberglass 10 Asbestos-cement					
Blank casing diameter: 5 in. to 60 ft., Dia. in. to .ft., Dia. in. to .ft.		Welded Threaded					
Casing height above land surface: 12 in., weight 2.8 lbs./ft. Wall thickness or gauge No. Sch. 40							
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)		11 Other (specify)					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)					
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes		10 Other (specify)					
2 Louvered shutter 4 Key punched 7 Torch cut							
SCREEN-PERFORATED INTERVALS: From 60 ft. to 80 ft., From .ft. to .ft.							
GRAVEL PACK INTERVALS: From 10 ft. to 80 ft., From .ft. to .ft.							
GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other							
Grout Intervals: From 0 ft. to 10 ft., From .ft. to .ft., From .ft. to .ft.							
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well					
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well		16 Other (specify below)					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage							
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage							
Direction from well? South		How many feet? 60					
FROM	TO	LITHOLOGIC LOG		FROM	TO	LITHOLOGIC LOG	
0	27	Clay					
27	34	Sand					
34	55	Clay					
55	80	Sand and Gravel					
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2/11/84 and this record is true to the best of my knowledge and belief. Kansas							
Water Well Contractor's License No. 186 This Water Well Record was completed on (mo/day/yr) 3/23/84							
under the business name of Kellys Water Well Service by (signature) <i>[Signature]</i>							
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.							

OFFICE USE ONLY

T

R

END

SEC.

35

SE 1/4

NE 1/4

SE 1/4

NE 1/4