

5 SCHULZ		WATER WELL RECORD		Form WWC-5	KSA 82a-1212	
LOCATION OF WATER WELL:		Fraction	Section Number	Township Number		Range Number
County: STAFFORD		NE 1/4 SE 1/4 NE 1/4	5	T 22 S		R 13 EW
Distance and direction from nearest town or city street address of well if located within city?						
SEWARD 1 1/4 E 1/4 S WESTSIDE.						
WATER WELL OWNER: L.D. DRILLING CO.						
R#, St. Address, Box #: RT. 1, BOX 183B						
City, State, ZIP Code: GREAT BEND, KS 67530						
Board of Agriculture, Division of Water Resources						
Application Number: T84-862						
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 80 ft. ELEVATION:				
NW NE SW SE		Depth(s) Groundwater Encountered 1. 42 ft. 2. ft. 3. ft.				
		WELL'S STATIC WATER LEVEL 12 ft. below land surface measured on mo/day/yr 11-12-84				
		Pump test data: Well water was ft. after hours pumping gpm				
		Est. Yield gpm: Well water was ft. after hours pumping gpm				
		Bore Hole Diameter 7 7/8 in. to 80 ft., and in. to ft.				
		WELL WATER TO BE USED AS:				
		5 Public water supply 8 Air conditioning 11 Injection well				
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)				
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well				
		Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted				
		Water Well Disinfected? Yes No				
TYPE OF BLANK CASING USED:		CASING JOINTS: Glued X Clamped				
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded						
2 PVC 4 ABS 7 Fiberglass Threaded						
Blank casing diameter 5 in. to 60 ft., Dia in. to ft., Dia in. to ft.						
Casing height above land surface 12 in., weight 2.65 lbs./ft. Wall thickness or gauge No. 214						
TYPE OF SCREEN OR PERFORATION MATERIAL:		10 Asbestos-cement				
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)						
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)						
SCREEN OR PERFORATION OPENINGS ARE: 118		8 Saw cut 11 None (open hole)				
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes						
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)						
SCREEN-PERFORATED INTERVALS: From 6.0 ft. to 80 ft., From ft. to ft.						
GRAVEL PACK INTERVALS: From 50 ft. to 80 ft., From ft. to ft.						
GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other						
Grout intervals: From 0 ft. to 10 ft., From ft. to ft., From ft. to ft.						
What is the nearest source of possible contamination: NONE		10 Livestock pens 14 Abandoned water well				
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well						
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)						
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage						
Direction from well?		How many feet?				
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG	
0	18	CLAY				
18	20	SANDY CLAY				
20	40	CLAY				
40	80	GRAVEL				
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-12-84 and this record is true to the best of my knowledge and belief. Kansas						
Water Well Contractor's License No. 389 This Water Well Record was completed on (mo/day/yr) 12-4-84						
Under the business name of PEISER WATER WELL SERV. INC. by (signature) Rudolph J. Peiser						
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.						