


LOCATION OF WATER WELL: Fraction SW 1/4 NW 1/4 SW 1/4 Section Number 7 Township Number T 22 S Range Number R 13 E
 County: Stacy
 Distance and direction from nearest town or city street address of well if located within city?
1 1/2 S of Seward, KS

WATER WELL OWNER: Big Bright
 RR#, St. Address, Box #: RR 1
 City, State, ZIP Code: Seward, KS
 Board of Agriculture, Division of Water Resources
 Application Number:

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 DEPTH OF COMPLETED WELL: 82 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1. 23' 3" ft. 2. 23' 3" ft. 3. 23' 3" ft.
 WELL'S STATIC WATER LEVEL 23' 3" ft. below land surface measured on mo/day/yr
 Pump test data: Well water was 8 ft. after 82 hours pumping 82 gpm
 Est. Yield 82 gpm: Well water was 8 ft. after 82 hours pumping 82 gpm
 Bore Hole Diameter 8 in. to 82 ft., and 82 in. to 82 ft.
 WELL WATER TO BE USED AS:
☒ Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
☐ 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
 Was a chemical/bacteriological sample submitted to Department? Yes (No); If yes, mo/day/yr sample was submitted
 Water Well Disinfected Yes No

TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
☒ PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded
 Blank casing diameter 5 in. to 72 ft., Dia. 5 in. to 72 ft., Dia. 5 in. to 72 ft.
 Casing height above land surface 18 in., weight 18 lbs./ft. Wall thickness or gauge No. 18

TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)
 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot ☒ 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 72 ft. to 82 ft., From 72 ft. to 82 ft.
 From 72 ft. to 82 ft., From 72 ft. to 82 ft.
 GRAVEL PACK INTERVALS: From 72 ft. to 82 ft., From 72 ft. to 82 ft.
 From 72 ft. to 82 ft., From 72 ft. to 82 ft.

GROUT MATERIAL: ☒ 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout intervals: From 5 ft. to 23 ft., From 23 ft. to 82 ft., From 82 ft. to 82 ft.

What is the nearest source of possible contamination:
☒ 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 How many feet? 80'

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	3	top soil			
3	35	clay			
35	40	sand			
40	71	clay			
71	82	gravel			

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-31-87 and this record is true to the best of my knowledge and belief. Kansas
 Water Well Contractor's License No. 4622 This Water Well Record was completed on (mo/day/yr) 5-12-87
 under the business name of Sam's Water Well by (signature) Sam Rayburn

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4