

USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:		County Stafford	Fraction NW 1/4 NW 1/4 NW 1/4	Section number 17	Township number T 22 S R 13 EW
2. Distance and direction from nearest town or city: 2 1/2 miles Southeast of Seward, KS Street address of well location if in city:			3. Owner of well: Gates Brothers R.R. or street: Route 1 City, state, zip code: Seward, KS 67577		
4. Locate with "X" in section below: N 1 Mile W E S 1 Mile			Sketch map: Approx. 100' East and 250' South of the NW Corner of Sec. 17		
5. Type and color of material			From	To	6. Bore hole dia. 9 in. Completion date 5-9-79 Well depth 76 ft.
Top soil			0	1	7. ☒ Cable tool ☒ Rotary ☐ Driven ☐ Dug ☐ Hollow rod ☐ Jetted ☐ Bored ☐ Reverse rotary
Sand - Fine			1	3	8. Use: ☐ Domestic ☐ Public supply ☐ Industry ☐ Irrigation ☐ Air conditioning ☒ Stock ☐ Lawn ☐ Oil field water ☐ Other
Sandy clay			3	11	9. Casing: Material styrene Height Above or below Threaded ☐ Welded ☒ Surface 18 in. RMP ☐ PVC ☐ Weight 1.5 lbs./ft. Dia. 5 in. to 66 1/2 ft. depth Wall Thickness: inches or Dia. ☐ in. to ☐ ft. depth gage No. 7 ga.
Sandy clay					10. Screen: Manufacturer's name Jess & Lowell Type Styrene 200 Dia. 5" Slot gauge 1/8" hole Length 10' Set between 65 ft. and 75 ft. ft. and ☐ ft. Gravel pack? Yes Size range of material 3/8-200
Sandy clay & gravel streaks			11	19	11. Static water level: ☐ mo./day/yr. 14' 6" below land surface Date 5-9-79
Sandy clay & gravel streaks & caliche			19	23	12. Pumping level below land surfaces: N/C ☐ ft. after ☐ hrs. pumping ☐ g.p.m. ☐ ft. after ☐ hrs. pumping ☐ g.p.m. Estimated maximum yield ☐ g.p.m.
Sandy clay - Tan & Gray - Hard, Caliche @ 30'			23	40	13. Water sample submitted: ☐ mo./day/yr. ☐ Yes ☒ No Date ☐
Soft sandy clay			40	44	14. Well head completion: ☐ Pitless adapter 18 Inches above grade
Hard Sandy Clay			44	46	15. Well grouted? Yes With: ☒ Neat cement ☐ Bentonite ☐ Concrete Depth: From 0 ft. to 10 ft.
Sandy clay & hard sandstone			46	47	16. Nearest source of possible contamination: FIELD ft. ☐ Direction ☐ Type ☐ Well disinfected upon completion? ☒ Yes ☐ No
Sandy clay - Gray			47	52	17. Pump: ☒ Not installed Manufacturer's name ☐ Model number ☐ HP ☐ Volts ☐ Length of drop pipe ☐ ft. capacity ☐ g.p.m. Type: ☐ Submersible ☐ Turbine ☐ Jet ☐ Reciprocating ☐ Centrifugal ☐ Other
Fine sand & gravel with gray clay			52	57	
Gray clay			57	58	
Fine sand & gravel			58	61	
Medium sand & gravel			61	75	
(Use a second sheet if needed)					
18. Elevation: Topography: ☐ Hill ☐ Slope ☐ Upland ☐ Valley		19. Remarks:		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Clarke Well & Eq., Inc. 185 Business name Great Bend, KS 67530 License No. Address 5-11-79 Signed Don Clarke Date 5-11-79 Authorized representative	

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5