

H VEATCH #1
WATER WELL RECORD

Form WWC-5 KSA 82a-1212


LOCATION OF WATER WELL: Fraction C-5 1/4 SE 1/4 NW 1/4 Section Number 29 Township Number T 22 S Range Number R 13 E
County: STAFFORD
Distance and direction from nearest town or city street address of well if located within city?

SEWARD 1/4 E 1/2 S EASTSIDE.

WATER WELL OWNER: D.P. LAUCK OIL CO. INC.
R#, St. Address, Box #: 221 S. Broadway Suite 400
City, State, ZIP Code: Wichita, KS 67202

H. VEATCH, ST. JOHNS, KS.
Board of Agriculture, Division of Water Resources
Application Number: J84-506

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL: 65 ft. ELEVATION: 8-6-84



Depth(s) Groundwater Encountered 1. 49 ft. 2. 49 ft. 3. 49 ft.

WELL'S STATIC WATER LEVEL 22 ft. below land surface measured on mo/day/yr 8-6-84

Pump test data: Well water was 2 ft. after 2 hours pumping 2 gpm

Est. Yield 2 gpm: Well water was 2 ft. after 2 hours pumping 2 gpm

Bore Hole Diameter: 7 7/8 in. to 65 ft., and 65 in. to 65 ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well

Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No

TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped

1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded

2 PVC 4 ABS 7 Fiberglass Threaded

Blank casing diameter 5 in. to 45 ft., Dia. 45 in. to 45 ft., Dia. 45 in. to 45 ft.

Casing height above land surface 12 in., weight 2-65 lbs./ft. Wall thickness or gauge No. 214

TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement

1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)

2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1/8 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes

2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 45 ft. to 65 ft., From 45 ft. to 65 ft., From 45 ft. to 65 ft.

GRAVEL PACK INTERVALS: From 35 ft. to 65 ft., From 35 ft. to 65 ft., From 35 ft. to 65 ft.

From 35 ft. to 65 ft., From 35 ft. to 65 ft., From 35 ft. to 65 ft.

From 35 ft. to 65 ft., From 35 ft. to 65 ft., From 35 ft. to 65 ft.

From 35 ft. to 65 ft., From 35 ft. to 65 ft., From 35 ft. to 65 ft.

From 35 ft. to 65 ft., From 35 ft. to 65 ft., From 35 ft. to 65 ft.

From 35 ft. to 65 ft., From 35 ft. to 65 ft., From 35 ft. to 65 ft.

From 35 ft. to 65 ft., From 35 ft. to 65 ft., From 35 ft. to 65 ft.

From 35 ft. to 65 ft., From 35 ft. to 65 ft., From 35 ft. to 65 ft.

From 35 ft. to 65 ft., From 35 ft. to 65 ft., From 35 ft. to 65 ft.

From 35 ft. to 65 ft., From 35 ft. to 65 ft., From 35 ft. to 65 ft.

From 35 ft. to 65 ft., From 35 ft. to 65 ft., From 35 ft. to 65 ft.

From 35 ft. to 65 ft., From 35 ft. to 65 ft., From 35 ft. to 65 ft.

From 35 ft. to 65 ft., From 35 ft. to 65 ft., From 35 ft. to 65 ft.

From 35 ft. to 65 ft., From 35 ft. to 65 ft., From 35 ft. to 65 ft.

From 35 ft. to 65 ft., From 35 ft. to 65 ft., From 35 ft. to 65 ft.

From 35 ft. to 65 ft., From 35 ft. to 65 ft., From 35 ft. to 65 ft.

From 35 ft. to 65 ft., From 35 ft. to 65 ft., From 35 ft. to 65 ft.

From 35 ft. to 65 ft., From 35 ft. to 65 ft., From 35 ft. to 65 ft.

From 35 ft. to 65 ft., From 35 ft. to 65 ft., From 35 ft. to 65 ft.

From 35 ft. to 65 ft., From 35 ft. to 65 ft., From 35 ft. to 65 ft.

From 35 ft. to 65 ft., From 35 ft. to 65 ft., From 35 ft. to 65 ft.

From 35 ft. to 65 ft., From 35 ft. to 65 ft., From 35 ft. to 65 ft.

From 35 ft. to 65 ft., From 35 ft. to 65 ft., From 35 ft. to 65 ft.

From 35 ft. to 65 ft., From 35 ft. to 65 ft., From 35 ft. to 65 ft.

From 35 ft. to 65 ft., From 35 ft. to 65 ft., From 35 ft. to 65 ft.

From 35 ft. to 65 ft., From 35 ft. to 65 ft., From 35 ft. to 65 ft.

From 35 ft. to 65 ft., From 35 ft. to 65 ft., From 35 ft. to 65 ft.

From 35 ft. to 65 ft., From 35 ft. to 65 ft., From 35 ft. to 65 ft.

From 35 ft. to 65 ft., From 35 ft. to 65 ft., From 35 ft. to 65 ft.

From 35 ft. to 65 ft., From 35 ft. to 65 ft., From 35 ft. to 65 ft.

From 35 ft. to 65 ft., From 35 ft. to 65 ft., From 35 ft. to 65 ft.

From 35 ft. to 65 ft., From 35 ft. to 65 ft., From 35 ft. to 65 ft.

From 35 ft. to 65 ft., From 35 ft. to 65 ft., From 35 ft. to 65 ft.

From 35 ft. to 65 ft., From 35 ft. to 65 ft., From 35 ft. to 65 ft.

From 35 ft. to 65 ft., From 35 ft. to 65 ft., From 35 ft. to 65 ft.

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-6-84 and this record is true to the best of my knowledge and belief. Kansas

Water Well Contractor's License No. 389 This Water Well Record was completed on (mo/day/yr) 8-18-84

Under the business name of REISER WATER WELL SERVICE, INC. by (signature) Rudolph Reiser

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top

three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL

OWNER and retain one for your records.

DJ