

1 LOCATION OF WATER WELL: County: Stafford		Fraction NC ¼ N side ¼ NW ¼	Section Number 29	Township Number T 22 S	Range Number R 14W E/W
Distance and direction from nearest town or city street address of well if located within city? 4S Radium, Ks.					
2 WATER WELL OWNER: Paul R. Neeland RR#, St. Address, Box # : RR 3 City, State, ZIP Code : Great Bend, Ks. 67530					
Board of Agriculture, Division of Water Resources Application Number: 14,442					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL . 95 ft. ELEVATION: unknown			
N E S W		Depth(s) Groundwater Encountered 1. 30 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 30 ft. below land surface measured on mo/day/yr 7-11-97 Pump test data: Well water was 88 ft. after 4 hours pumping 670 gpm Est. Yield 650 gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter . 30 in. to 95 ft., and . in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes.....No..... If yes, mo/day/yr sample was sub- mitted			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter 16 in. to 75 ft., Dia. 16.5 in. to ft., Dia. in. to ft. Sch. 40 Casing height above land surface 12 in., weight 16.5 lbs./ft. Wall thickness or gauge No. Sch. 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 75 ft. to 95 ft., From ft. to ft. GRAVEL PACK INTERVALS: From 20 ft. to 70 ft., From 73 ft. to 95 ft. From ft. to ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 0 ft. to 20 ft., From 70 ft. to 73 ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? How many feet? no source - in field How many feet?					
LITHOLOGIC LOG FROM TO PLUGGING INTERVALS FROM TO 0 45 top soil and clay 45 70 fine sand 70 76 clay 76 93 sand and gravel 93 95 clay					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) ... 7-11-97... and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 186.... This Water Well Record was completed on (mo/day/yr) ... 7-29-97... under the business name of Kelly's Water Well Service, Inc. by (signature) Kathryn L. Reed					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					