

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Stafford</u>		SE 1/4 NW 1/4 SE 1/4	11	T 22 S	R 14W E/W

Distance and direction from nearest town or city street address of well if located within city?

1S, 1 1/2W of Seward, Ks.

2 WATER WELL OWNER: Jim Williams		Sterling Drilling Company		Steckel Farms 1-11	
RR#, St. Address, Box #: P. O. Box 80307		P. O. Box 1006		Board of Agriculture, Division of Water Resources	
City, State, ZIP Code: Boulder, CO 80307		Pratt, Ks. 67124		Application Number:	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 94 ft. ELEVATION: unknown	
		Depth(s) Groundwater Encountered 1. 45 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 45 ft. below land surface measured on mo/day/yr 12/02/02. Pump test data: Well water was ft. after hours pumping gpm Est. Yield 50 gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 8 in. to 94 ft., and in. to ft. WELL WATER USED AS: 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted	
5 TYPE OF BLANK CASING USED:		Water Well Disinfected? Yes No	
1 Steel 3 RMP (SR) 2 PVC 4 ABS		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded	
Blank casing diameter 5 in. to 74 in. Dia		Casing height above land surface 3 ft. below in., weight lbs./ft. Wall thickness or gauge No.	
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement	
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)		12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:		8 Saw cut 11 None (open hole)	
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)			
SCREEN-PERFORATED INTERVALS: From 74 ft. to 94 ft. From ft. to ft.			
GRAVEL PACK INTERVALS: From 20 ft. to 94 ft. From ft. to ft.			

6 GROUT MATERIAL:		3 Bentonite 4 Other	
Grout Intervals: From 45 ft. to 40 ft. From 20 ft. to 3 ft. From ft. to ft.			
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well	
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage			
Direction from well?		How many feet?	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
			94	45	sand and gravel
			45	40	bentonite
			40	20	top soil
			20	3	bentonite
			3	0	top soil

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12/02/02 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 186 This Water Well Record was completed on (mo/day/yr) 12/04/02 under the business name of Kelly's Water WELL Service, Inc. by (signature) Kathryn L. Good	
--	--