

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: <u>Stafford</u>		<u>SE ¼ SE ¼ SW ¼</u>		<u>10</u>		<u>T 22 S</u>		<u>R 14 E/W</u>	
Distance and direction from nearest town or city street address of well if located within city?									
<u>1 3/4 South, 2 1/2 East of Radium</u>									
2 WATER WELL OWNER: <u>Charlie Keeler</u>									
RR#, St. Address, Box # : <u>1621 Tyler</u>						Board of Agriculture, Division of Water Resources			
City, State, ZIP Code : <u>Great Bend, Ks. 67530</u>						Application Number: <u>SFWW2563</u>			
3 LOCATE WELL'S LOCATION WITH		4 DEPTH OF COMPLETED WELL. 75 ft. ELEVATION:							
AN "X" IN SECTION BOX:		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.							
		WELL'S STATIC WATER LEVEL 30 ft. below land surface measured on mo/day/yr 3-27-03							
		Pump test data: Well water was ft. after hours pumping gpm							
		Est. Yield <u>N/A</u> gpm: Well water was ft. after hours pumping gpm							
		Bore Hole Diameter. 9 in. to 75 ft., and in. to ft.							
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well							
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)							
		2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well Stock							
Was a chemical/bacteriological sample submitted to Department? Yes. No. X ; If yes, mo/day/yrs sample was submitted									
Water Well Disinfected? Yes <u>HTH</u> No									

5 TYPE OF BLANK CASING USED:		5 Wrought iron		8 Concrete tile		CASING JOINTS: Glued. ☒ Clamped. ☐	
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)			Welded	
2 PVC	4 ABS	7 Fiberglass				Threaded.	
Blank casing diameter 5 in. to 60 ft., Dia in. to ft., Dia in. to ft.							
Casing height above land surface. 24 in., weight SDR- 26 lbs./ft. Wall thickness or gauge No.							
TYPE OF SCREEN OR PERFORATION MATERIAL:				7 PVC		10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)	11 Other (specify)			
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:				5 Gauzed wrapped		8 Saw cut	
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes		11 None (open hole)		
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)				ft.
SCREEN-PERFORATED INTERVALS: From 75 ft. to 60 ft., From ft. to ft.							
From 75 ft. to 20 ft., From ft. to ft.							
GRAVEL PACK INTERVALS: From 75 ft. to 20 ft., From ft. to ft.							
From ft. to ft., From ft. to ft.							
6 GROUT MATERIAL:		1 Neat cement	2 Cement grout	3 Bentonite	4 Other	Hole plug	
Grout intervals: From 20 ft. to 0 ft., From ft. to ft., From ft. to ft.							
What is the nearest source of possible contamination:				10 Livestock pens		14 Abandoned water well	
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well			
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)			
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	None			
Direction from well?				How many feet?			

[illegible]

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-27-03 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 134 This Water Well Record was completed on (mo/day/yr) 4-1-03 under the business name of Rosencrantz- Bemis by (signature) [Signature]

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone 785-296-5524. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.