

1 LOCATION OF WATER WELL: County: Stafford Fraction: NW 1/4 NE 1/4 SW 1/4 Section Number: 11 Township Number: T 22 S Range Number: R 14W E/W

Distance and direction from nearest town or city street address of well if located within city? 1/2S, 1 1/2W of Seward, Ks.

2 WATER WELL OWNER: Steckel Farms L. D. Drilling, Inc. Steckel Farms 1-11 Board of Agriculture, Division of Water Resources RR#, St. Address, Box #: P. O. Box 3245 7SW 26th Ave. Application Number: 20030216 City, State, ZIP Code: Boulder, Co. Great Bend, Ks. 67530

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram of section box with X in SW quadrant] 4 DEPTH OF COMPLETED WELL: 91 ft. ELEVATION: unknown. WELL'S STATIC WATER LEVEL: 48 ft. below land surface measured on mo/day/yr 09/03/03. Pump test data: Well water was ... ft. after ... hours pumping ... gpm. Est. Yield ... 60 ... gpm: Well water was ... ft. after ... hours pumping ... gpm. Bore Hole Diameter: .8 ... in. to .91 ... ft., and ... in. to ... ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well. Was a chemical/bacteriological sample submitted to Department? Yes. No; If yes, mo/day/yrs sample was submitted. Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued. Clamped. 2 PVC 4 ABS 7 Fiberglass 9 Other (specify below) Welded. Threaded. Blank casing diameter: 5 in. to 7.1 ft., Dia. in. to ... ft., Dia. in. to ... ft. Casing height above land surface: 12 in., weight: 2.8 lbs./ft. Wall thickness or gauge No. Sch. 40. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole). SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) ft. SCREEN-PERFORATED INTERVALS: From: 71 ft. to 91 ft., From: ft. to ft. GRAVEL PACK INTERVALS: From: 20 ft. to 91 ft., From: ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other. Grout Intervals: From: 0 ft. to 20 ft., From: ft. to ft., From: ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage. Direction from well? North How many feet? 100

Table with columns: FROM, TO, LITHOLOGIC LOG, FROM, TO, PLUGGING INTERVALS. Rows: 0-9 top sand, 9-63 sandy clay, 63-91 sand and gravel.

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 09/03/03 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 186 This Water Well Record was completed on (mo/day/yr) 09/12/03 under the business name of Kelly's Water Well Service, Inc. by (signature) Kathryn L. Head