

1 LOCATION OF WATER WELL:

County: Stafford

Distance and direction from nearest town or city street address of well if located within city?
1S, 1 1/2W. 1S of Seward, KS

Fraction

NE ¼ SE ¼ SW ¼

Section Number

14

Township Number

T 22 S

Range Number

R 14w E/W

2 WATER WELL OWNER:

Morris Garvin Trust

RR#, St. Address, Box # : Morris Kay Trustee

City, State, ZIP Code : P.O. Box 1773
Lawrence, KS 66044

Global Positioning Systems (decimal degrees, min. of 4 digits)

Latitude: _____

Longitude: _____

Elevation: _____

Datum: _____

Data Collection Method: _____

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N

W

-- NW --

-- NE --

-- SW --

-- SE --

X

E

S

4 DEPTH OF COMPLETED WELL

100

ft.

Depth(s) Groundwater Encountered (1)35 (2) (3) ft.

WELL'S STATIC WATER LEVEL35 ft. below land surface measured on mo/day/yr.01/28/08.

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield60 gpm: Well water was ft. after hours pumping gpm

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr

Sample was submitted. Water well disinfected? Yes No

5 TYPE OF CASING USED:

1 Steel 3 RMP (SR) 5 Wrought Iron 8 Concrete tile

2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below)

7 Fiberglass

CASING JOINTS: Glued Clamped

Welded

Threaded

Blank casing diameter 5 in. to 80 ft., Diameter in. to ft., Diameter in. to ft.

Casing height above land surface3 ft. below in., Weight 2.8 lbs./ft. Wall thickness or gauge No. Sch. 40

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 9 ABS 11 Other (Specify)

2 Brass 4 Galvanized Steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot 3 Mill slot 5 Gauzed wrapped 7 Torch cut 9 Drilled holes 11 None (open hole)

2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 80 ft. to 100 ft., From ft. to ft.

From ft. to ft., From ft. to ft.

GRAVEL PACK INTERVALS: From 20 ft. to 100 ft., From ft. to ft.

From ft. to ft., From ft. to ft.

6 GROUT MATERIAL:

1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 3 ft. to 35 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide Storage 16 Other (specify below)

2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 14 Abandoned water well

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer Storage 15 Oil well/gas well

Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
			100	35	gravel
		Garvin - Marmie 1-14 2nd	35	3	bentonite
			3	0	top soil
		Sterling Drilling Company			
		P. O. Box 1006			
		Pratt, KS 67124			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION:

This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 01/28/08 and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 186 This Water Well Record was completed on (mo/day/year) 02/05/08 under the business name of Kelly's Water Well Service, Inc. by (signature) Kathryn L Good

INSTRUCTIONS:

Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. Visit us at <http://www.kdheks.gov/waterwell/index.html>.

KSA 82a-1212