

1 LOCATION OF WATER WELL:		Fraction	Township Number	Range Number	
County: STAFFORD		NE ¼ NE ¼ NE ¼	T 22 S	R 14 E	
Distance and direction from nearest town or city street address of well if located within city?					
Radium 15 SE Southside					
2 WATER WELL OWNER: STERLING DRILLING CO.					
RR#, St. Address, Box #: BOX 129					
City, State, ZIP Code: STERLING, KS 67579					
Board of Agriculture, Division of Water Resources Application Number: T85-714					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 60 ft. ELEVATION:			
A diagram of a section box divided into four quadrants labeled NW, NE, SW, and SE. A north arrow points upwards. The box is labeled 'N' at the top, 'S' at the bottom, 'W' on the left, and 'E' on the right.		Depth(s) Groundwater Encountered 1. .ft. 2. .ft. 3. .ft.			
		WELL'S STATIC WATER LEVEL 26.5 ft. below land surface measured on mo/day/yr 7-27-85			
		Pump test data: Well water was . ft. after . hours pumping . gpm			
		Est. Yield . gpm; Well water was . ft. after . hours pumping . gpm			
		Bore Hole Diameter 7.18 in. to 6.0 ft., and .in. to .ft.			
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter 5 in. to 40 ft., Dia .in. to .ft., Dia .in. to .ft. Casing height above land surface 12 in., weight 2.65 lbs./ft. Wall thickness or gauge No. 2-14 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1/8 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 40 ft. to 60 ft., From .ft. to .ft. From .ft. to .ft., From .ft. to .ft. GRAVEL PACK INTERVALS: From 31 ft. to 60 ft., From .ft. to .ft. From .ft. to .ft., From .ft. to .ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout intervals: From 0 ft. to 10 ft., From .ft. to .ft., From .ft. to .ft.					
What is the nearest source of possible contamination: NONE					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? How many feet?					
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	SANDY SOIL			
2	25	- CLAY			
25	30	FINE SAND			
30	60	GRAVEL			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-27-85 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 389 This Water Well Record was completed on (mo/day/yr) 7-29-85 under the business name of REISER WATER WELL SERV. INC. by (signature) Reiser					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					