


1 LOCATION OF WATER WELL: County: <u>Stafford</u>	Fraction <u>NW</u> $\frac{1}{4}$ <u>SW</u> $\frac{1}{4}$ <u>SW</u> $\frac{1}{4}$	Section Number <u>26</u>	Township Number <u>T</u> <u>22</u> <u>S</u>	Range Number <u>R</u> <u>14</u> <u>5W</u>
--	---	-----------------------------	--	--

Distance and direction from nearest town or city street address of well if located within city?

4½ south 2 1/8 west of Seward, Ks.

2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :	<u>Kurt Rugan</u> <u>Rt. 2</u> <u>Ellinwood, Ks. 67526</u>	Board of Agriculture, Division of Water Resources Application Number: <u>SFWW0206</u>
---	--	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: <u>80</u> ft. ELEVATION: Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL <u>42</u> ft. below land surface measured on mo/day/yr <u>1-3-95</u> Pump test data: Well water was ft. after hours pumping gpm Est. Yield <u>na</u> gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter <u>10</u> in. to <u>80</u> ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply <u>1</u> Domestic 2 Irrigation 3 Feedlot 4 Industrial 6 Oil field water supply 7 Lawn and garden only 8 Air conditioning 9 Dewatering 10 Monitoring well <u>Live Stock</u> 11 Injection well 12 Other (Specify below) Was a chemical/bacteriological sample submitted to Department? Yes.....No <u>X</u> If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <u>hth</u> No
---	---

5 TYPE OF BLANK CASING USED: 1 Steel <u>2 PVC</u> Blank casing diameter <u>5</u> in. to <u>60</u> ft., Dia. in. to ft., Dia. in. to ft. Casing height above land surface <u>2</u> in., weight <u>258</u> lbs./ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter SCREEN-PERFORATED INTERVALS: From <u>60</u> ft. to <u>80</u> ft., From ft. to ft. GRAVEL PACK INTERVALS: From <u>80</u> ft. to <u>20</u> ft., From ft. to ft.	3 Wrought iron 6 Asbestos-Cement 7 Fiberglass 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut	8 Concrete tile 9 Other (specify below) 10 Asbestos-cement 8 RMP (SR) 9 ABS 8 Saw cut 9 Drilled holes 10 Other (specify)	CASING JOINTS: Glued <u>X</u> Clamped Welded Threaded 11 None (open hole)
---	--	---	--

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other <u>hole plug</u> Grout Intervals: From <u>0</u> ft. to <u>20</u> ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? <u>north west</u> How many feet? <u>1000'</u>
--

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Top soil			
3	12	Brown clay			
12	21	Gray clay			
21	26	Brown clay			
26	32	Gray sandy clay			
32	50	Sandy brown clay & streaks of fine sand			
50	60	Sand and gravel medium some clay streaks			
60	78	Sand and gravel clean coarse loose.			
78	80	Brown clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>1-3-95</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>134</u> This Water Well Record was completed on (mo/day/yr) <u>1-6-95</u> under the business name of <u>Rosencrantz-Bemis</u> by (signature) <u>Freda Hedson</u>
