

1 LOCATION OF WATER WELL:		Fraction		Section Number	Township Number		Range Number	
County: Pawnee		SW 1/4 SE 1/4 NE 1/4		2	T 22 S		R 15 E/W	
Distance and direction from nearest town or city street address of well if located within city? 7 1/2 east, 1/2 south of Larned, Ks.								
2 WATER WELL OWNER:		John Blackwell			Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box # :		Rt. 2			Application Number:			
City, State, ZIP Code :		Larned, Ks. 67550						
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 80. ft. ELEVATION:						
<div style="text-align: center;"><p>1 mile</p></div>		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.						
		WELL'S STATIC WATER LEVEL 46. ft. below land surface measured on mo/day/yr 12-6-96						
		Pump test data: Well water was ft. after hours pumping gpm						
		Est. Yield na gpm: Well water was ft. after hours pumping gpm						
		Bore Hole Diameter 9.7/8 in. to 80. ft. and in. to ft.						
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well						
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)								
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well		Live Stock						
Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> If yes, mo/day/yr sample was submitted								
Water Well Disinfected? Yes <u>hth</u> No								
5 TYPE OF BLANK CASING USED:		5 Wrought iron		8 Concrete tile		CASING JOINTS: Glued <u>X</u> Clamped		
1 Steel 3 RMP (SR)		6 Asbestos-Cement		9 Other (specify below)		Welded		
2 PVC 4 ABS		7 Fiberglass				Threaded		
Blank casing diameter 5 in. to 60. ft. Dia. in. to ft. Dia. in. to ft.								
Casing height above land surface 2 ft. weight SDR 26 lbs./ft. Wall thickness or gauge No.								
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC		10 Asbestos-cement		11 Other (specify)		
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)				12 None used (open hole)				
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS								
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped		8 Saw cut		11 None (open hole)		
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes				10 Other (specify)				
2 Louvered shutter 4 Key punched 7 Torch cut								
SCREEN-PERFORATED INTERVALS:		From 60. ft. to 80. ft.		From ft. to ft.		From ft. to ft.		
GRAVEL PACK INTERVALS:		From 80. ft. to 20. ft.		From ft. to ft.		From ft. to ft.		
6 GROUT MATERIAL:		1 Neat cement 2 Cement grout		3 Bentonite 4 Other		hole plug		
Grout Intervals: From 20. ft. to 0. ft. From ft. to ft. From ft. to ft.								
What is the nearest source of possible contamination:								
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well								
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well								
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)								
13 Insecticide storage								
Direction from well?		north west		How many feet?		100'		
FROM TO LITHOLOGIC LOG		FROM TO PLUGGING INTERVALS						
0 3 Top soil								
3 11 Brown sandy clay								
11 27 Gray and brown clay								
27 79 Sand and gravel medium loose, clean								
79 80 Brown clay								
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-6-96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 134 This Water Well Record was completed on (mo/day/yr) 12-28-96 under the business name of Rosencrantz-Bemis by (signature) Fredia Rodson								
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.								

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4