I LOCATION OF WATER WELL: Fraction NE
Distance and direction from nearest town or city street address of well if located within city? From Larned, Ks. 42 South, 8 3/4 East 2 WATER WELL OWNER: G10r1a Crane RH#, St. Address, Box # : Rt. 2 City, State, ZIP Code : Larned, Ks. 67550 3 LOCATE WELL'S LOCATION WITH 4 DEPTH OF COMPLETED WELL 0.8
From Larned, Ks. 4½ South, 8 3/4 East 2 WATER WELL OWNER: GLOT1a Crane RR#, St. Address, Box # : Rt. 2 City, State, ZiP Code : Larned, Ks. 67550 Application Number: 3 LOCATE WELL'S LOCATION WITH 4 DEPTH OF COMPLETED WELL 0.8 ft. ELEVATION: Application Number: An "X" IN SECTION BOX:
WATER WELL OWNER: Gloria Crane
RR#, St. Address, Box # : Rt. 2 City, State, ZIP Code : Larned, Ks. 67550
City, State, ZIP Code : Larned, Ks. 67550 South Agricultus, Division of Water Resource Application Number: 3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:
AN "X" IN SECTION BOX: Depth(s) Groundwater Encountered 1
WELL'S STATIC WATER LEVEL
Pump test data: Well water was ft. after hours pumping graph with the strain from the strain f
Est. Yield L.M.A
WELL WATER TO BE USED AS: 5 Public water supply 9 Dewatering 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well
Was a chemical/bacteriological sample submitted to Department? Yes
Was a chemical/bacteriological sample submitted to Department? Yes
TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) 2 PVC 4 ABS 7 Fiberglass Threaded Blank casing diameter 5 in. to 48 ft., Dia in. to 5 Ibs./ft. Wall thickness or guage No. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Guazed wrapped 8 Saw cut 11 None (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Guazed wrapped 9 Drilled holes
TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) 2 PVC 4 ABS 7 Fiberglass Threaded Blank casing diameter 5 in. to 48 ft., Dia in. to 5 Ibs./ft. Wall thickness or guage No. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Guazed wrapped 8 Saw cut 11 None (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Guazed wrapped 9 Drilled holes
TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded Welded Threaded In. to Casing diameter 5 in. to 48 ft., Dia in. to Casing height above land surface 24 in., weight SDR 25 lbs./ft. Wall thickness or guage No. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 Other (Specify) 2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Guazed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded Delay Threaded Delay Threade
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded Delay Threaded Delay Threade
2 PVC 4 ABS 7 Fiberglass Threaded Blank casing diameter 5 in to 48 ft., Dia in to 5 in to 6 ft., Dia in to 6 ft., Dia in to 7 FVC 10 Asbestos-Cement 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 Other (Specify) 12 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 12 None used (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
Blank casing diameter 5 in to 48 ft Dia in to 5 ft Dia in to 5 lbs./ft Wall thickness or guage No 1
Casing height above land surface
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 Other (Specify)
1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 Other (Specify)
2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Guazed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
2 Louvered shutter 4 Key supplied 7 Torch cut 10 Other (specify)
The control of the co
SCREEN-PERFORATED INTERVALS: From
From
GRAVEL PACK INTERVALS: From
Tion
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other hole plug
Grout Intervals: From
What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage Septic Tank
Direction from well? South How many feet? 59
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS
0 3 Sandy top soil
3 7 Sandy brown clay
7 13 Gray clay
13 33 Fine sand & clay
33 68 Sand & gravel small, med, loose
with small clay streaks
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and wa
completed on (mo/day/year)
completed on (mo/day/year)
completed on (mo/day/year)