USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

## WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

|   | County           | Fraction Near Center |    | Section number   |   | Township number  | Range number  |             |  |
|---|------------------|----------------------|----|--|---|--|---|-------------|--|
| 1. Location of well:  | Pawnee           | 1/4NW 1/4 NW         |    | 28   |   | T 22 S   | R 15  |             |  |
| 10 Miles SE of Larned  R.R. or s  Street address of well location if in city: |                  |                      |    | er of well: Keith Rolo<br>street: 512 West 13th<br>ote, zip code: Larned, KS 67550 |   |  |   |             |  |
| 4. Locate with "X" i  |                  | Sketch map:          |    |  |   | 6. Bore hole dia. 9 in Well depth 50 ft.   | . Completion date 1-4-  | <u>-7</u> 8 |  |
| *w  | NE<br>!          |                      |    |  | -   | 7 Cable tool Rotary Hollow rod Jetted 8. Use: Domestic Po  | Driven Dug<br>Bored _X_ Reverse ro  |             |  |
| S<br>S<br>Mile  |                  |                      |    |  | İ   | LawnOil field waterOther  9. Casing: MateriaStyren Beight: Above or below Threaded Welded Surface12 in.  RMP PVC Weight1.5lbs./ft.  Dia5 in. to ft. depth! Wall Thickness: inches or |   |             |  |
| 5. Type and color of  |                  |                      |    | From   | То  | Dia in. to ft. dep  10. Screen: Manufacturer's r   | th gage No. <u>. 200</u>  | _           |  |
| Top soil  |                  |                      |    | 0  | 3   | Ixpe Styrene 200   | Lowell 5"   | _           |  |
| Brown clay  |                  |                      |    | 3  | 13  |  | ft. and50   | _ ft.       |  |
| Sandy clay  |                  |                      | 13 | 20   | Gravel pack? <u>VES</u> Size ra   | and  | <u>5</u> 6.   |             |  |
| Sand & gravel & thin clay at 39   |                  |                      | 20 | 50   | 11. Static water level: mo./day/yr. 22 6t. below land surface Dote 1-4-78 |  |   |             |  |
|   |                  |                      |    |  |   | 12. Pumping level below land ft. after l ft. after l Estimated maximum yield   | nrs. pumpingg.p<br>nrs. pumpingg.p  | .m.         |  |
|   |                  |                      |    |  |   | 13. Water sample submitted:  |   |             |  |
|   |                  |                      |    |  |   | Pitless adapter  | 12 Inches above grade   |             |  |
|   |                  |                      |    |  |   | 15. Well grouted? <u>Ves</u> With: X Neat cement Depth: From O ft. to  | Bentonite Concr<br>10 ft.   | ete         |  |
|   |                  |                      |    |  |   | 16. Nearest source of possible ft Direction Well disinfected upon comple   | Туре  | )   '       |  |
|   |                  |                      |    |  |   | 17. Pump: Manufacturer's name  | X Not installed   |             |  |
|   |                  |                      |    |  | 1   | Length of drop pipe  | HP Volts<br>ft. capacityg.p   | .m.         |  |
|   |                  |                      |    |  |   | Type: Submersible Jet  | Turbine   | g           |  |
|   | (Use o second st | neet if needed)      |    |  |   | Centrifugal  | Other   | , s         |  |
| Topography:  Hill Slope Upland Valley   | 19. Remarks:     |                      |    |  | C   | 20. Water well contractor's of This well was drilled under me is true to the best of my known larke Well & Ed Business name Address Great Bend Authorized rep                        | y jurisdiction and this repo<br>ledge and belief.<br>a. Inc. 185<br>d. 55 67530 | 1/4         |  |