

1 LOCATION OF WATER WELL:		Fraction	Form WWC-5	KSA 82a-1212	Section Number	Township Number	Range Number
County: Pawnee		Near $\frac{1}{4}$ C/N $\frac{1}{2}$ $\frac{1}{4}$ NE $\frac{1}{4}$ $\frac{1}{4}$			33	T 22 S	R 15 E/W
Distance and direction from nearest town or city street address of well if located within city? 2 3/4 north, 6 1/8 east of Zook							
2 WATER WELL OWNER: Milford Zook							
RR#, St. Address, Box # : Rt. 2				Board of Agriculture, Division of Water Resources			
City, State, ZIP Code : Larned, Ks. 67530				Application Number: 33,937-B			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 45 ft. ELEVATION:					
		Depth(s) Groundwater Encountered 1. 21 ft. 2. ft. 3. ft.					
		WELL'S STATIC WATER LEVEL 26 1/2 ft. below land surface measured on mo/day/yr 11-26-82					
		Pump test data: Well water was 40 ft. after 1 hours pumping 300 gpm					
		Est. Yield 300 gpm: Well water was ft. after hours pumping gpm					
		Bore Hole Diameter: 29 in. to 45 ft. and in. to ft.					
		WELL WATER TO BE USED AS:					
		5 Public water supply		8 Air conditioning		11 Injection well	
		1 Domestic		3 Feedlot		6 Oil field water supply	
		2 Irrigation		4 Industrial		7 Lawn and garden only	
		6 Dewatering		10 Observation well		12 Other (Specify below)	
Was a chemical/bacteriological sample submitted to Department? Yes.....No. <u>X</u>; If yes, mo/day/yr sample was submitted							
Water Well Disinfected? Yes <u>HTH</u> No							
5 TYPE OF BLANK CASING USED:							
1 Steel		3 RMP (SR)		5 Wrought iron		8 Concrete tile	
2 PVC		4 ABS		6 Asbestos-Cement		9 Other (specify below)	
				7 Fiberglass			
Blank casing diameter 16 in. to 35 ft., Dia. in. to ft., Dia. in. to ft.							
Casing height above land surface 24 in., weight lbs./ft. Wall thickness or gauge No. 7							
TYPE OF SCREEN OR PERFORATION MATERIAL:							
1 Steel		3 Stainless steel		5 Fiberglass		7 PVC	
2 Brass		4 Galvanized steel		6 Concrete tile		8 RMP (SR)	
						9 ABS	
						10 Asbestos-cement	
						11 Other (specify)	
						12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:							
1 Continuous slot		3 Mill slot		5 Gauzed wrapped		8 Saw cut	
2 Louvered shutter		4 Key punched		6 Wire wrapped		9 Drilled holes	
				7 Torch cut		10 Other (specify)	
						11 None (open hole)	
SCREEN-PERFORATED INTERVALS: From 35 ft. to 45 ft., From ft. to ft.							
GRAVEL PACK INTERVALS: From 10 ft. to 45 ft., From ft. to ft.							
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other							
Grout Intervals: From 0 ft. to 10 ft., From ft. to ft., From ft. to ft.							
What is the nearest source of possible contamination:							
1 Septic tank		4 Lateral lines		7 Pit privy		10 Livestock pens	
2 Sewer lines		5 Cess pool		8 Sewage lagoon		11 Fuel storage	
3 Watertight sewer lines		6 Seepage pit		9 Feedyard		12 Fertilizer storage	
						13 Insecticide storage	
						14 Abandoned water well	
						15 Oil well/Gas well	
						16 Other (specify below)	
						NONE	
Direction from well? How many feet?							
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG		
0	2	Top soil					
2	10	Brown clay					
10	21	Light brown clay and fine sand					
21	40	Sand and gravel					
40	45	Clay					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-31-83 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 134 This Water Well Record was completed on (mo/day/yr) 6-27-83 under the business name of Rosencrantz-Bemis Ent. by signature [Signature]							
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.							

OFFICE USE ONLY

T

R

END

SEC.

33

C 1/4

1/4

ME 1/4

DP