WATE	ER WE	CLL RECORD	Form W	VWC-5	Division of Water Resources App. No.		
1 LOCATION OF WATER WELL:		Fraction		Section Number Township No. Range Number			
County: Pawnee			1/4 NW 1/4 N	N 1/4 SW 1/4	27 T 22 S R 15 □E ☑W	V	
Stre	Street/Rural Address of Well Location; if unknown, distance & direction				Global Positioning System (GPS) information:		
from nearest town or intersection: If at owner's address, check here .				Latitude: .38.10888 (in decimal degrees))		
3 1/2 North, 6 1/4 East of Zook				Longitude: 098.96745 (in decimal degrees))		
				Elevation:			
2 WATER WELL OWNER: Alice L Howard Rev Trust				☐ Datum: ☐ WGS 84, ☑ NAD 83, ☐ NAD 27 Collection Method:			
RR#, Street Address, Box #: 2112 Meadowlark Road					GPS unit (Make/Model:)		
City, State, ZIP Code : Manhattan, KS 66502-4557				7	☐ Digital Map/Photo, ☐ Topographic Map. ☐ Land Survey		
					Est. Accuracy:		
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 75 ft.							
		OY: Denth(s) Convert	COMPLETED WEL	ft.			
SEC	SECTION BOX: Depth(s) Groundwater Encountered (1)				ft. (2) ft. (3) ft.		
	Pump test data: Wall water was				below land surface measured on mo/day/yr. 10-15-15		
FST VIFI D N/A gram Well water was					ft. after hours pumping gpm		
W NW NE E EST. YIELD. N/Agpm. Well water was							
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well Domestic Feedlot Oil field water supply Dewatering Other (Specify below)							
☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well							
<u> </u>	Was a chemical/bacteriological sample submitted to Department? Yes V No						
	S If yes, mo/day/yr sample was submitted						
	I mile	Water well disint	fected? Yes	No			
CASIN	5 TYPE OF CASING USED: ☐ Steel ☑ PVC ☐ Other						
Casir	Casing diameter .16 in. to .75 ft., Diameter in. to ft., Diameter ft.						
Casing height above land surface. 18 in., Weight Sch 40 lbs./ft., Wall thickness or gauge No.							
TYPE	TYPE OF SCREEN OR PERFORATION MATERIAL:						
	Steel Stainless Steel PVC Other (Specify)						
Brass Galvanized Steel None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE:							
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)							
Louvered shutter Key punched Wire wrapped							
SCREEN-PERFORATED INTERVALS: From						,	
GPANEL DACK INTERNALS, E					ft., From ft. to ft.		
	UKAV	EL PACK INTERVALS:	From	π. to	ft., From ft. to ft.		
From ft. to ft., From ft. to ft.							
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other Grout Intervals: From ft. to ft. From 20 ft to ft. From ft. to ft.							
Grout Intervals: From ft. to ft., From 20 ft. to ft., From ft. to ft.							
☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fi				Fuel storage			
Watertight sewer lines Seepage pit Feedyard Fertilizer s							
Direc	ction fro	m well		Distance 1	from well		
FROM	ТО	LITHOLOGI	C LOG	FROM	TO LITHO. LOG (cont.) or PLUGGING INTERVALS	_	
0	2	Top soil					
2	14	Sandy tan & brown clay					
14	40	Small to med gravel & sa	and			\neg	
		with clay streaks				\dashv	
40	45	Brown clay				\dashv	
45	64	Sandstone				-	
64	75	Fire clay				-	
						\dashv	
						\dashv	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ✓ constructed, ☐ reconstructed, or ☐ plugged							
under my jurisdiction and was completed on (mo/day/year) 12-23-13 and this record is true to the best of my knowledge and best of							
Kansas Water Well Contractor's License No. 134 This Water Well Record was completed on (molden/see) 12-20-15							
under the business name of Noseticialitz- beinis Ent inc by (signature)							
INSTRUCTIONS. Use type writer of Dali Doint Ben. PLEASE PRESS FIRMLY and PRINT clearly Diegse fill in blooks and shook the assertion of the second shook the se							
Kaisas Department of Mealth and Environment, Bureau of Water Geology Section, 1000 SW, Jackson St. Suita 420, Table 17, 12, 12, 12, 13							
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell/index.html							
				waterweit/Index	4444	- 1	