	<u> </u>	ATER WELL RECORD	Form WWC-	5 KSA 82a-	1212		
LOCATION OF WAT		•		ction Number	Township Nu	mber	Range Number
County: Pawnee	NW NW	1/4 SW 1/4 S		2	т 22	S	R 15 <b>K</b> /w
Distance and direction f	from nearest town or city stre		· ·				
		uth 7½ east of	<u>f Larned</u>	, Ks.			
WATER WELL OWN		ie					
	# : Rt. 2-Box 9					riculture, (	Division of Water Resource
City, State, ZIP Code	: Larned, Ks.	67550			Application	Number:	26528
LOCATE WELL'S LC AN "X" IN SECTION	CATION WITH 4 DEPTH (	OF COMPLETED WELL oundwater Encountered	.17.3	ft. ELEVAT	TION:		
	WELL'S ST.	ATIC WATER LEVEL	.46. ft.t	nelow land surfa	ace measured on a	It. ວ mo/day/vr	.7-28-94
	·						mping gpm
NW -	Est. Yield .	.13.00. gpm: Well wa	ter was88	ft. aft	er 2	hours pu	mping . 130.0 gpm
¥ w 1							to
<u> </u>	1 1 1	ER TO BE USED AS:	5 Public water		3 Air conditioning		Injection well
SW	SE 1 Dome		6 Oil field wa	iter supply 9	9 Dewatering	12	Other (Specify below)
X i	2 Irrigat	<del></del>	7 Lawn and	garden only 1	0 Monitoring well	<i>. ,</i>	
	Was a chem	ical/bacteriological sample	submitted to D				mo/day/yr sample was sub
<u> </u>	mitted			Wate	er Well Disinfected	? Yes H	TH No
TYPE OF BLANK CA		5 Wrought iron	8 Concr	ete tile	CASING JOIN	ITS: Glued	IXClamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other	(specify below)	)	Weld	ed
2 PVC	4 ABS	7 Fiberglass				Threa	ded
	1.6 in. to 9.3						
Casing height above lar	nd surface12	in., weight		lbs./ft	. Wall thickness or	gauge No	D <i></i>
TYPE OF SCREEN OR	PERFORATION MATERIAL	.:	7 PV	<u>c                                    </u>	10 Asbe	stos-ceme	nt
1 Steel	3 Stainless steel	5 Fiberglass	8 RM	IP (SR)	11 Othe	r (specify)	
2 Brass	4 Galvanized steel	6 Concrete tile	9 <b>A</b> E	S	12 None	used (op	en hole)
SCREEN OR PERFORA	ATION OPENINGS ARE:	5 Gau	zed wrapped		8 Saw cut		11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire	wrapped		9 Drilled holes		, ,
2 Louvered shutte	r 4 Key punched	7 Torc	h cut		10 Other (specify)		
SCREEN-PERFORATE	O INTERVALS: From	9.3 ft. to .	113	ft From	133	ft. to	517.3
							o
GRAVEL PAC							520
	From	ft. to					
GROUT MATERIAL:	· · · · · · · · · · · · · · · · · · ·	2 Cement grout	3 Bento				25 to 127
•	0ft. to . 2.0.	· ·					
	rce of possible contamination		,	10 Livesto			pandoned water well
_	4 Lateral lines	7 Pit privy			torage		
2 Sewer lines	5 Cess pool	8 Sewage lag	2000		•		
	r lines 6 Seepage pit	9 Feedyard	goon		er storage		ther (specify below)
_	illes o Seepage pit	9 reedyaid					none
Direction from well? FROM TO	LITHOLO	GIC LOG	FROM	How many		IGGING IN	NTERVALS
		<u> </u>	7110101			radiita ii	TILITALO
1 1	Top soil Brown & gray cl	av		<del> </del>	····		
				<del> </del>			
28   48   5	Sand and gravel	3 V		<del> </del>			
	Brown & gray cl	. •	i i	! I			
1 1	Sand and gravel			1 1			
	Brown sandy cla						
	Sand and clay m						
140   173	Sand and gravel	clean coarse	e loose	<b>-</b>			
		ARRESTED I S. I.		ļ			
				<b> </b>			
				ļ			
				ļ			
	A	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~					PROMA AND THE COURT OF THE COUR
				ļ			
		WW 15.00					
CONTRACTOR'S O	R LANDOWNER'S CERTIFIC	CATION: This water well v	was (1) constru	cted. (2) recon	structed, or (3) plu	laged und	er my jurisdiction and was
	ear)						
	License No						
	e of Rosencrantz		Hecolu Wa				10 1
				by (signatu			Dodson
INSTRUCTIONS: Use type	ewriter or ball point pen. PLEASE PRE	ESS FIRMLY and PRINT clearly. P	lease fill in blanks,	underline or circle to	he correct answers. Ser	d top three o	opies to Kansas Department