

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: Pawnee		NE 1/4 SW 1/4 SW 1/4		28		T 22 S		R 16 EW	
Distance and direction from nearest town or city street address of well if located within city? 4 3/4 miles south of Larned, Ks.									
2 WATER WELL OWNER: Mary Kathryn Hanshew									
RR#, St. Address, Box # : 11817 Edgemont Circle Board of Agriculture, Division of Water Resources									
City, State, ZIP Code : Oklahoma City, OKla 73162 Application Number:									
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 180 ft. ELEVATION:							
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 42 ft. below land surface measured on mo/day/yr 11-7-97 Pump test data: Well water was ft. after hours pumping gpm Est. Yield na. gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter was in. to ft., and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well 12 Other (Specify below) stock well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X							
		5 TYPE OF BLANK CASING USED:							
		1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded Blank casing diameter 5 in. to 160 ft. Dia in. to ft. Dia in. to ft. Casing height above land surface 2 in. weight SDR 26 lbs./ft. Wall thickness or gauge No.							
		TYPE OF SCREEN OR PERFORATION MATERIAL:							
		1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)							
SCREEN-PERFORATED INTERVALS: From 160 ft. to 180 ft. From ft. to ft.									
GRAVEL PACK INTERVALS: From 201 ft. to 110 ft. From 96 ft. to 42 ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other hole plug 110' to 96'									
Grout Intervals: From 42 ft. to 0 ft. From ft. to ft. From ft. to ft.									
What is the nearest source of possible contamination:									
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage none									
Direction from well? How many feet?									
FROM	TO	LITHOLOGIC LOG				FROM	TO	PLUGGING INTERVALS	
		reconstructed old irrigation well.							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-7-97 and this record is true to the best of my knowledge and belief. Kansas									
Water Well Contractor's License No. 134 This Water Well Record was completed on (mo/day/yr) 12-2-97									
under the business name of Rosencrantz-Bemis by (signature) Fredia Redson									
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.									

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4